

PRODUCT CATALOG



Made in Germany www.German-Adler.com, Frankfurt am Main/GERMANY

GERMAN ADLER GmbH

Company Profile


GERMAN ADLER GmbH is an internationally operating company in the lubricant industry with its headquarters located in Frankfurt/Main, in central Germany.

Our core business is the global selling of motor oils, gear oils, hydraulic oils, industrial and agricultural oils, greases as well as additives, antifreezes, winter chemi-cals and brake fluids. Since each item of our wide product range

Wade in Germany

is manufactured in Germany, it is created in a certified production process and therefore meets the highest quality standards.

Our company places great value on good cooperation and is characterised by flexibility and reliability. On these grounds we develop new market strategies together with our business partners and provide them with advisory support. One of our



GERMAN ADLER GmbH combines German quality with a global view of a market-oriented vision. Because the quality label 'Made in Germany' is an international value.

PRODUCT RANGE

GERMAN ADLER's range of products

- · Motor Oils
- · Gear Oils
- · Hydraulic Oils
- · Steering Fluids
- · Motor Cycle Oils
- · Agricultural Oils
- · Construction Oils
- · Greases
- · Antifreezes
- · Brake Fluids
- · Car Care Products
- · Industrial Oils
- · Metal Working Oils
- · Additives
- · Classic Car Oils

If you cannot find the product of your choice or a particular packaging unit in our catalog, please do not hesitate to contact us. We will be pleased to receive your request.

export@German-Adler.com info@German-Adler.com

www.German-Adler.com

OIL FOR PASSENGER CARS Page	
RMAN ADLER SYNT SAE 0W-16 04	
RMAN ADLER SYNT SAE 0W-20 04	
RMAN ADLER SYNT SAE 0W-20 F 04	
RMAN ADLER SYNT SAE 0W-20 FE 05	
RMAN ADLER SYNT SAE 0W-30 05	
RMAN ADLER SYNT SAE 0W-30 VO 05	
RMAN ADLER <i>SYNT SAE</i> 0W-30 S 06	
RMAN ADLER SYNT SAE 0W-40 06	
RMAN ADLER SYNT SAE 5W-20 06	
RMAN ADLER SYNT SAE 5W-30 SLD 07	
RMAN ADLER SYNT SAE 5W-30 C1 07	
RMAN ADLER SYNT SAE 5W-30 FO-RL 07	
RMAN ADLER SYNT SAE 5W-30 07	
RMAN ADLER SYNT SAE 5W-30 DPF 08	
RMAN ADLER SYNT SAE 5W-30 DPF-S 08	
RMAN ADLER SYNT SAE 5W-30 C4 08	
RMAN ADLER SYNT SAE 5W-30 D 09	
RMAN ADLER SYNT SAE 5W-40 MS 09	
RMAN ADLER SYNT SAE 5W-40 F 10	
RMAN ADLER SYNT SAE 5W-40 C3 10	
RMAN ADLER SYNT SAE 5W-50 11	
RMAN ADLER SYNT SAE 10W-30 11	
RMAN ADLER SYNT SAE 10W-40 11	
RMAN ADLER SYNT SAE 10W-40 HC 12	
RMAN ADLER RACING SYNT SAE 10W-60 12	
RMAN ADLER SAE 15W-40 HD 12	
RMAN ADLER SAE 20W-50 HD 12	
RMAN ADLER SAE 15W-40 GST	
RMAN ADLER SAE 20W-50 GST 14	
OT FOR COMMERCIAL VEHICLES	
ROIL FOR COMMERCIAL VEHICLES Page	
RMAN ADLER TX SYNT SAE 5W-30 HC-LS 15	
RMAN ADLER TX SYNT SAE 10W-40 15	
RMAN ADLER TX SYNT SAE 10W-40 HC-LA 16	
RMAN ADLER TX SYNT SAE 10W-30 CK-4 17	
RMAN ADLER TX SYNT SAE 10W-40 CK-4 17	
RMAN ADLER TX SAE 15W-40 CK-4 18	
RMAN ADLER TX SAE 15W-40 18	
RMAN ADLER TX SAE 20W-50 PLUS 18	
FUNCTIONAL OILS Page	
DAMAN A DI ED A ODA GAE A OW DO	
RMAN ADLER AGRA SAE 10W-30 20	
RMAN ADLER AGRA SAE 10W-40 20	
RMAN ADLER AGRA SAE 15W-30 21	
RMAN ADLER UTTO SAE 10W-30 21	
RMAN ADLER SAE 30 TO-4 22	
RMAN ADLER SAE 50 TO-4 22	
THE PROPERTY OF THE PROPERTY O	

HYDRAULIC- AND STEERING FLUIDS	Page		
S501 GERMAN ADLER LH-M PLUS	47	CONTACT	Page
S502 GERMAN ADLER ZH-M PLUS S509 GERMAN ADLER ZH-M PLUS F SYNT	47 48	GERMAN ADLER HEAD OFFICE FRANKFURT	64
BRAKE FLUIDS	Page	TRANSPORT	Page
B119 GERMAN ADLER BRAKE FLUID DOT 4	50	PACKAGING FOR CONTAINERS	65
B114 GERMAN ADLER BRAKE FLUID DOT 5.1	50	PACKAGING FOR TRUCK	65
INDUSTRIAL OILS / HYDRAULIC FLUIDS	Page		
H004 GERMAN ADLER HLP 22	51		
H005 GERMAN ADLER HLP 32	51		
H006 GERMAN ADLER HLP 46	52		
H007 GERMAN ADLER HLP 68 H008 GERMAN ADLER HLP 100	52 52		
11000 GERMAN ADEER HEP 100	32		
RADIATOR ANTIFREEZE / COOLANT	Page		
W017 GERMAN ADLER ANTIFREEZE	54		
W018 GERMAN ADLER ANTIFREEZE G	54		
W175 GERMAN ADLER ANTIFREEZE READY MIX -5°C	54		
W185 GERMAN ADLER ANTIFREEZE READY MIX -5°C G	54		
W041 GERMAN ADLER ANTIFREEZE READY MIX -25°C W042 GERMAN ADLER ANTIFREEZE READY MIX -25°C G	55 55		
W051 GERMAN ADLER ANTIFREEZE READY MIX -38°C	55		
W052 GERMAN ADLER ANTIFREEZE READY MIX -38°C G	55		
W014 GERMAN ADLER ANTIFREEZE 12 PLUS	56		
W145 GERMAN ADLER ANTIFREEZE READY MIX 12 PLUS -5°C	56		
W048 GERMAN ADLER ANTIFREEZE READY MIX 12 PLUS -25°C			
W049 GERMAN ADLER ANTIFREEZE READY MIX 12 PLUS -37°C W013 GERMAN ADLER ANTIFREEZE GA13	57 57		
W135 GERMAN ADLER ANTIFREEZE GA13 READY MIX -5°C	57 57		
W061 GERMAN ADLER ANTIFREEZE GA13 READY MIX -35 °C	58		
ADDITIVE	Page		
D110 GERMAN ADLER OCTANE BOOSTER	60		
D120 GERMAN ADLER CETANE BOOSTER D130 GERMAN ADLER INJECTION CLEANER	60 60		
D140 GERMAN ADLER INGLETION CLEANER D140 GERMAN ADLER ENGINE FLUSH	61		
D150 GERMAN ADLER RADIATOR LEAK STOP	61		
D160 GERMAN ADLER ANTI SMOKE	61		
D170 GERMAN ADLER DPF CLEANER	62		
D180 GERMAN ADLER RADIATOR CLEANER	62		
D190 GERMAN ADLER DIESEL SYSTEM CLEANER	62		
D200 GERMAN ADLER OIL TREATMENT	63		

63

D215 GERMAN ADLER CATALYST CLEANER

Art.-N° **M133 GERMAN ADLER SYNT SAE OW-16**

Contents

1 l bottle

- 4 | canister 5 I canister
- 20 I pail
- 60 I drum
- 200 I drum

Description

- fully synthetic motor oil
- high performance lubricant
- for many gasoline engines of passenger cars where low viscosity oils are predilected
- excellent lubricity and wear protection
- stable lubrication film
- very good cold starting properties even at low temperatures
- high engine cleanliness
- lowered oil consumption in conjunction with high fuel efficiency

Specification / Recommendation

API SP ILSAC GF-6B



Art.-N° **M134 GERMAN ADLER SYNT SAE OW-20**

Contents

- 1 l bottle
- 4 | canister
- 5 I canister
- 20 I pail
- 60 I drum
- 200 I drum

Description

- fully synthetic motor oil
- high performance lubricant
- for the most gasoline engines of passenger cars
- excellent lubricity
- stable lubrication film at all operation conditions
- very good cold starting properties even at low temperatures
- long motor life/complex wear protection/cleanliness
- low oil consumption/high fuel efficiency

Specification / Recommendation

API SP Chrysler MS-6395 Daihatsu Ford WSS-M2C947-A Ford WSS-M2C947-B1 Ford WSS-M2C962-A GM dexos1 Gen 3 Honda Hyundai ILSAC GF-6A Isuzu Kia

Lexus Mazda Nissan Subaru Suzuki Toyota



UPDATE

Art.-N° M135 **GERMAN ADLER SYNT SAE OW-20 F**

Contents

- 1 l bottle
- 4 | canister
- 5 I canister
- 20 I pail
- 60 I drum 200 I drum

Description

- fully synthetic low friction motor oil
- maximum thermal and mechanical stability
- excellent viscosity temperature/low evaporation loss
- very good cold starting properties even at low temperatures
- reduces fuel consumption
- highly effective dispersant additives

Specification / Recommendation

ACEA C5/C6 API SP/SP RC Ford WSS-M2C956-A1 ILSAC GF-6A Porsche C20 VW 508 00/509 00 VW TL 52577





Art.-N° **M136 GERMAN ADLER SYNT SAE OW-20 FE**

Contents

Description

- 1 l bottle
- 4 I canister
- 5 I canister
- 20 I pail
- 60 I drum
- 200 I drum
- fully synthetic low friction motor oil
- for modern fuel economy passenger cars and light vans
- superb thermal and mechanical stability
- excellent viscosity-temperature profile
- very good cold starting properties even at low temperatures
- reduces fuel consumption
- highly effective dispersant additives

Specification / Recommendation

ACEA C5 API SP (RC) BMW LL17FE+ BMW LL14FE+ Chrysler MS-12145 Fiat 9.55535-GSX Ford WSS-M2C947-B1 Ford WSS-M2C962-A1 ILSAC GF-6A JLR STJLR 03-5006-16 MB 229.71 MB 229.72 Opel OV0401547



Art.-N° **M067 GERMAN ADLER SYNT SAE OW-30**

Contents

Description

- 1 l bottle
- 4 | canister
- 5 I canister
- 20 I pail
- 60 I drum
- 200 l drum
- fully synthetic low friction motor oil
- maximum thermal and mechanical stability
- excellent viscosity temperature/low evaporation loss
- most modern antifriction additives
- reduces fuel consumption
- maximum wear protection/best low temperature
- highly effective dispersant additives
- especially developed for the latest engine generation of VW with extended oil-drain-intervals (WIV) including the pump injection engines

Specification / Recommendation

ACEA C3 API SN BMW Longlife-04 MB 229.51/229.31 MB 229.52 Porsche C30 VW 504 00/507 00



GERMAN ADLER SYNT SAE OW-30 VO Art.-N° **M066**

Contents

Description

- 1 l bottle
- 4 | canister
- 5 | canister
- 20 I pail 60 I drum
- 200 I drum
- fully synthetic high performance motor oil
- specifically developed additive package for use in Volvo engines
- excellent lubrication safety
- low oil consumption
- high fuel efficiency

Specification / Recommendation

ACEA A5/B5 API SL Volvo VCC 95200377



Art.-N° **M166 GERMAN ADLER SYNT SAE OW-30 S**

Contents

- 1 l bottle
- 4 I canister
- 5 I canister
- 20 I pail
- 60 I drum
- 200 l drum

Description

- fully synthetic low friction motor oil
- maximum thermal and mechanical stability
- for gasoline engines
- most modern antifriction additives
- reduces fuel consumption
- maximum wear protection/best low temperature
- highly effective dispersant additives
- especially developed for the latest engine generation of VW with extended oil-drain-intervals (WIV) including the pump injection engines

Specification / Recommendation

ACEA C2 API SP Chrysler MS-6395 Daihatsu GM dexos1 Gen 3 GM 60945-M Honda ILSAC GF-6A Isuzu Kia Lexus Mazda Nissan Subaru

Suzuki Toyota



Art.-N° **M020 GERMAN ADLER SYNT SAE OW-40**

Contents

- 1 l bottle 4 I canister
- 5 I canister
- 20 I pail
- 60 I drum 200 I drum

Description

- fully synthetic low friction motor oil
- excellent suitability for all modern gasoline and diesel engines
- especially advisable for turbocharger and direct injection (DI)
- smooth cold start/very good lubrication on high temperatures
- high quality additives for anti-wear properties, dispersant and detergent
- extreme shear stability/high oxidation resistance
- extended engine life/less maintenance-costs/ reduced oil and fuel consumption

Specification / Recommendation

ACEA A3/B4 API SN/CF BMW Longlife-01 Ford WSS-M2C937-A MB 226.5/229.5 Porsche A40 Renault RN 0700/0710 VW 502 00/505 00



Art.-N° **M186 GERMAN ADLER SYNT SAE 5W-20**

UPDATE

Contents

1 l bottle

- 4 I canister
- 5 I canister
- 20 I pail
- 60 I drum 200 I drum

Description

- fully synthetic high performance motor oil
- especially designed for gasoline/diesel passenger cars and light vans
- low viscosity/fuel saving
- stable lubrication film even at low temperatures
- long motor life due to complex wear protection/ cleanliness
- low oil consumption/high fuel efficiency/ reduced exhaust gas emissions
- long oil drain intervals

Specification / Recommendation

API SP Chrysler MS-6395 Daihatsu Ford WSS-M2C945-A Ford WSS-M2C945-B1 Ford WSS-M2C930-A Ford WSS-M2C960-A GM dexos1 Gen 3 GM 6094-M Honda Hyundai ILSAC GF-6A Isuzu Kia Lexus

Mazda Nissan Subaru Suzuki Toyota





Art.-N° **M118 GERMAN ADLER SYNT SAE 5W-30 SLD**

Contents

Description

- 1 l bottle
- 4 | canister
- 5 I canister
- 20 I pail
- 60 I drum
- 200 I drum
- synthetic high performance motor oil
- four seasons oil for passenger cars with gasoline and diesel engines
- low Sulphated Ash, Phosphorus, Sulphur (low SAPS)
- especially designed for diesel particulate filter (DPF)
- protects environment/low pollution
- high performance additives/optimal wear protection/ best motor cleanliness
- excellent thermal oxidation stability
- longer drain intervals at maximum motor protection
- best low temperature properties
- longer operating life of the engine

Specification / Recommendation

ACEA C3/C2 API SP API SN PLUS/CF BMW Longlife-04 MB 229.52/229.51 MB 229.31 Opel GM Dexos 2 VW 505 01/502 00/ 505 00



Art.-N° **M109 GERMAN ADLER SYNT SAE 5W-30 C1**

Contents

Description

- 1 l bottle
- 4 | canister
- 5 I canister
- 20 I pail
- 60 l drum
- 200 l drum
- synthetic high performance/low friction motor oil
- for the latest generations of passenger cars and vans with diesel and gasoline engines
- low Sulphated Ash, Phosphorus, Sulphur (low SAPS)
- developed for engines with diesel particulate filter (DPF)
- best motor cleanliness/reduced friction/long lifetime of the engine
- maximum fuel economy by dropped high temperature viscosity (HTHS)
- minimized wear by fast engine oiling
- maximum pollution prevention due to minimized oil related emissions

Specification / Recommendation

ACEA C1 Jaguar/Land Rover STJLR.03.5005 JASO DL-1 Mazda DPF Mitsubishi DPF



Art.-N° **M060** GERMAN ADLER SYNT SAE 5W-30 FO-RL

Contents

1 l bottle

- 4 | canister
- 5 | canister
- 20 I pail
- 60 I drum
- 200 I drum

Description

- synthetic high performance/low friction motor oil
- for the latest generations of passenger cars and vans with diesel and gasoline engines
- high wear and corrosion protection
- excellent cleanliness of engine/long motor life
- fuel and oil economy

Specification / Recommendation

ACEA A5/B5 API SL Jaguar/Land Rover STJLR.03.5003 Ford WSS M2C913-B/C/D Renault RN 0700



Art.-N° **M185 GERMAN ADLER SYNT SAE 5W-30**

Contents

- 1 l bottle
- 4 | canister
- 5 I canister
- 20 I pail
- 60 I drum
- 200 I drum

Description

- fully synthetic low friction motor oil
- for all passenger car gasoline and diesel engines
- reduced oil and fuel consumption
- excellent dispersancy
- keeps motor clean
- very good low-temperature properties/smooth cold start
- modern oxidation inhibitors
- increased service life of the oil

Specification / Recommendation

ACEA A3/B4 API SP/CF



Art.-N° **M125 GERMAN ADLER SYNT SAE 5W-30 DPF**

Contents

1 l bottle

- 4 | canister 5 I canister
- 20 I pail
- 60 I drum
- 200 I drum

Description

- synthetic high performance motor oil
- especially for high power gasoline and diesel engines, newest models of passenger cars, sports cars and light commercial vehicles
- reduction of particle built-up/low ash
- compatible with the newest diesel particulate filters (DPF)
- very good low temperature properties
- low friction/excellent wear protection
- effective cleaning additives/extended oil drain intervals
- excellent motor protection and reduced of fuel consumption

Specification / Recommendation

ACEA C3 API SN/CF BMW Longlife-04 MB 229.51 VW 504 00/507 00



Art.-N° M126 GERMAN ADLER SYNT SAE 5W-30 DPF-S

Contents

Description

- 1 | bottle 4 I canister
- 5 I canister
- 20 I pail
- 60 I drum
- 200 I drum
- synthetic high performance motor oil designed for high power gasoline and diesel engines
- reduction of particle built-up/low ash
- compatible with the newest diesel particulate filters (DPF)
- very good low temperature properties
- low friction/excellent wear protection
- effectively cleaning additives/extended oil drain intervals
- lowered fuel consumption

Specification / Recommendation

ACEA C3 API SN/CF BMW Longlife-04 MB 229.51 VW 504 00/507 00



GERMAN ADLER SYNT SAE 5W-30 C4 Art.-N° M121

Contents

1 l bottle

- 4 I canister
- 5 I canister
- 20 I pail
- 60 I drum 200 I drum

Description

- high performance synthetic low friction motor oil
- for gasoline and diesel engines with particulate filter (DPF)
- reduction of particle built-up
- low Sulphated Ash, Phosphorus, Sulphur (low SAPS)
- very good low temperature properties
- high wear and corrosion protection
- excellent cleanliness of engine/long motor life
- fuel and oil economy

Specification / Recommendation

ACEA C4-10 MB 226.51/229.31/ 229.51 Renault RN 0720 equipped with DPF



Art.-N° **M122 GERMAN ADLER SYNT SAE 5W-30** D

NEW

Contents

- 1 l bottle
- 4 | canister
- 5 I canister
- 20 I pail 60 I drum
- 200 I drum
- Description
- fully synthetic high performance motor oil
- for gasoline engines
- best wear protection / maximum motor cleanliness
- best low-temperature properties / cold start properties
- reduction of fuel and oil consumption

Specification / Recommendation

API SP Daihatsu Fiat 9.55535-CR1 Ford WSS-M2C929-A Ford WSS-M2C946-A Ford WSS-M2C946-B1 Ford WSS-M2C961-A GM dexos1 Gen 3 GM 6094M/4718M Honda/Acura HTO-06 Hyundai ILSAC GF-6A Isuzu Kia Lexus Mazda

Opel OV 040 1547-G30

Nissan

Subaru Suzuki Toyota



Art.-N° M149 **GERMAN ADLER SYNT SAE 5W-40 MS**

Contents

1 | bottle

- 4 I canister
- 5 | canister
- 20 I pail
- 200 I drum
- 60 I drum

Description

- fully synthetic high performance motor oil
- for gasoline and diesel particulate filter (DPF)
- low Sulphated Ash, Phosphorus, Sulphur (low SAPS)
- best wear protection/maximum motor cleanliness
- best low-temperature properties/cold start properties
- longer operating life of the engine by rapid oil circulation
- reduction of fuel and oil consumption

Specification / Recommendation

ACEA C3 API SN/CF API SN PLUS BMW Longlife-04 Fiat 9.55535-S2 Ford WSS-M2C917-A GM Dexos 2 MB 226.5/229.31 MB 229.51

Porsche A40 Renault RN 0700/0710

VW 502 00/505 00/505 01(PN)

Art.-N° **M068 GERMAN ADLER SYNT SAE 5W-40**

Contents

- 1 l bottle
- 4 | canister
- 5 I canister
- 20 I pail
- 60 I drum
- 200 I drum

Description

- high performance synthetic low friction motor oil
- for gasoline and diesel engines of passenger cars
- especially for fuel injected and turbo charged engines
- excellent cold start and fast oil feed even lower than -30°C
- optimized high temperature viscosity
- high wear and corrosion protection
- excellent cleanliness of engine/long motor life
- fuel and oil economy

Specification / Recommendation

ACEA A3/B4 API SN/CF BMW Longlife 98 Fiat 9.55535-M2 MB 229.3 Opel GM-LL-B-025 Porsche A40 PSA B71 2296 Renault RN 0710/0700 VW 502 00/505 00



Art.-N° M168 GERMAN ADLER SYNT SAE 5W-40 L

NEW

Contents

1 | bottle

4 | canister

5 I canister

20 I pail

60 l drum

200 l drum

Description

- high performance synthetic low friction motor oil
- for gasoline and diesel engines of passenger cars
- especially for fuel injected and turbo charged engines
- all seasons use in areas of strong daily or seasonal thermal fluctuations
- optimized high temperature viscosity
- high wear and corrosion protection
- excellent cleanliness of engine/long motor life
- fuel and oil economy

Specification / Recommendation

ACEA A3/B4 API SP



Art.-N° M001 GERMAN ADLER SYNT SAE 5W-40 F

UPDATE

Contents

- 1 | bottle
- 4 | canister
- 5 I canister
- 20 | pail
- 60 I drum
- 200 l drum

Description

- high performance synthetic motor oil
- designed for gasoline and diesel engines of passenger cars
- for fuel injected and turbo charged engines
- excellent cold start and fast oil feed even lower than -30°C
- reduced fuel consumption
- optimized high temperature viscosity/ low friction properties
- high wear and corrosion protection
- longer motor life/excellent cleanliness of engine
- excellent performance persists even at long drain intervals

Specification / Recommendation

ACEA A3/B4 API SP/CF BMW Longlife-01 BMW Longlife-98 Fiat 9.55535 M2 Lamborghini Maserati MB 229.3/229.5 MB 226.5 Opel GM-LL-B-025 Porsche A 40 PSA B71 2296 Renault RN 0700/0710 VW 502 00/505 00



Art.-N° M138 GERMAN ADLER SYNT SAE 5W-40 C3

Contents

- 1 | bottle
- 4 | canister
- 5 | canister
- 20 I pail
- 60 l drum 200 l drum

Description

- fully synthetic high performance motor oil
- designed for gasoline and diesel engines with unit injector and vans
- low friction oil of the new generation
- low Sulphated Ash, Phosphorus, Sulphur (low SAPS)
- decreased particle build-up in diesel particulate filter (DPF) Ford WSS-M2C917A
- assist the environmental protection by lowering pollution
- best wear protection/maximum motor cleanliness
- reduction of fuel and oil consumption

Specification / Recommendation

ACEA C3 ACEA A3/B4-04 API SN/CF BMW Longlife-04 Fiat 9.55535-S2 Ford WSS-M2C917A Opel GM dexos2 MB 229.31/229.51 Porsche A40 Renault RN 0700/0710 VW 502 00/ 505 00/505 01 (PN)



Art.-N° **M101 GERMAN ADLER SYNT SAE 5W-50**

Contents

- 1 l bottle
- 4 I canister
- 5 I canister
- 20 I pail
- 60 I drum
- 200 I drum

Description

- high performance synthetic low friction motor oil
- for gasoline and diesel engines of passenger cars
- especially for fuel injected and turbo charged engines
- excellent cold start and fast oil feed even lower than -30°C
- optimized high temperature viscosity
- high wear and corrosion protection
- excellent cleanliness of engine/longer motor life
- fuel and oil economy

Specification / Recommendation

ACEA A3/B4 API SN/CF BMW Longlife-98 MB 229.3 Opel GM-LL-B-025 Porsche A40 PSA B71 2296 Renault RN 0710/0700 VW 502 00/505 00



GERMAN ADLER SYNT SAE 10W-30 Art.-N° **M184**

Contents

- 1 l bottle
- 4 | canister
- 5 I canister
- 20 I pail
- 60 I drum
- 200 I drum

Description

- synthetic low friction motor oil
- for all passenger cars with gasoline and diesel engines
- reduced oil and fuel consumption
- excellent dispersancy/keeps motor clean
- very good low-temperature properties/smooth cold start
- modern oxidation inhibitors
- increased service life of the oil

Specification / Recommendation

ACEA A3/B4 API SN/CF MB 229.1 VW 505 00 Daihatsu Honda Hyundai Kia Lexus Mazda Mitsubishi Nissan Subaru Suzuki

Toyota



GERMAN ADLER SYNT SAE 10W-40 Art.-N° **M058**

Contents

- 1 l bottle
- 4 | canister
- 5 | canister
- 20 I pail 60 I drum
- 200 I drum

Description

- high performance synthetic motor oil
- designed for gasoline and diesel engines of passenger cars
- for fuel injected and turbo charged engines
- reduced fuel and oil consumption
- modern oxidation inhibitors/increased service life of the oil
- optimal wear protection cares for long engine life

Specification / Recommendation

ACEA A3/B3/B4 API SL/CF Fiat 9.55535-G2/D2 PSA B71 2296 Renault RN 0700 MB 229.1 VW 501 01/505 00



Art.-N° **M093 GERMAN ADLER SYNT SAE 10W-40 HC**

UPDATE

Contents

- 1 l bottle
- 4 | canister
- 5 I canister
- 20 I pail
- 60 I drum
- 200 I drum

Description

- high performance synthetic low friction motor oil
- for gasoline and diesel engines of passenger cars
- for turbo and non-turbo charged engines
- low evaporation loss
- very good cold start performance
- reduced consumption of fuel and oil
- excellent oxidative stability/keeps engine clean
- optimal wear protection cares for long engine life

Specification / Recommendation

ACEA A3/B4 API SP Fiat 9.55535-G2/D2 MB 229.1/229.3 PSA B71 2296 Renault RN 0700 VW 501 01/505 00



GERMAN ADLER RACING SYNT SAE 10W-60 Art.-N° **M070**

UPDATE

Contents

- 1 l bottle
- 4 | canister
- 5 I canister
- 20 I pail
- 200 I drum
- 60 I drum

Description

- fully synthetic racing performance motor oil
- for turbo charged and fuel injected engines
- special additive components
- excellent cold-starting properties
- optimal piston cleanliness
- maximum wear protection

Specification / Recommendation

ACEA A3/B4 API SP/CF



Art.-N° **M007 GERMAN ADLER SAE 15W-40 HD**

Contents

- 1 l bottle
- 4 | canister
- 5 I canister
- 20 I pail
- 60 I drum
- 200 I drum

Description

- high performance multigrade motor oil
- for gasoline and diesel engines of passenger cars
- lower fuel and oil consumption
- protection against black sludge
- keeps the engine clean
- modern oxidation inhibitors extend service life of the oil
- optimal wear protection cares for long engine life

Specification / Recommendation

ACEA A3/B3 ACEA A3/B4-08 API SL/CF Fiat 9.55535-G2/D2 MB 229.1 VW 501 01/505 00



GERMAN ADLER SAE 20W-50 HD Art.-N° **M011**

UPDATE

Contents

- 1 | bottle
- 4 I canister
- 5 I canister
- 20 | pail
- 60 l drum 200 I drum

Description

- high performance multigrade motor oil
- for gasoline and diesel engines of passenger cars
- lower fuel and oil consumption
- protection against black sludge
- keeps the engine clean
- modern oxidation inhibitors extend the service life of the oil
- optimal wear protection cares for long engine life

Specification / Recommendation

ACEA A3/B4 API SL/CF MB 229.1







GERMAN ADLER SAE 15W-40 GST Art.-N° **M009**

Contents Description

- 1 l bottle
- 4 | canister 5 I canister
- 20 I pail
- 60 I drum 200 I drum
- multigrade motor oil
- for gasoline and diesel engines - protection against black sludge
- protection against thermal oxidation, corrosion and wear
- all seasons oil



Art.-N° **M042 GERMAN ADLER SAE 20W-50 GST**

Contents 1 l bottle

- multigrade motor oil

- 4 | canister
- for gasoline and diesel engines
- 5 I canister
- protection against black sludge
- 20 I pail 60 I drum
- 200 I drum
- protection against thermal oxidation, corrosion and wear all seasons oil

Description

Specification / Recommendation

Specification / Recommendation

API SF/CD

API SF/CD



MOTOR OIL FOR COMMERCIAL VEHICLES

Art.-N° **T046** GERMAN ADLER TX SYNT SAE 5W-30 HC-LS

UPDATE

Contents

Description

5 I canister

- 20 I pail
- 60 I drum 200 I drum
- high performance synthetic motor oil
- for EURO 5 and EURO 6 class commercial engines
- under limits for sulphated ash, sulphur and phosphorus content (low SAPS)
- for trouble-free operating (particle filter)
- high wear protection/reduces friction
- low evaporation tendency/good elastomer compatibility
- very high oxidation resistance
- protects against corrosion and black sludge
- reduce oil consumption
- excellent viscosity/temperature behaviour
- high shaer stability
- great fuel economy characteristics

Specification / Recommendation

ACEA E7/E8/E11/E4 API CJ-4 CAT ECF-3 Cummins CES 20081

DAF **Detrot Diesel DDC**

93K218

Deutz DQC IV-10 LA

Iveco JASO DH 2

Mack EO-O Premium Plus

Mack EO-N Premium Plus

Mack EO-M Plus

MAN M 3677/M 3477/M 3691 MAN M 3271-1/M 3575

MB 228.51/228.31/235.28

MTU Type 3.1 and 2.1 Renault Truck RLD-3

Scania LA und LDF 4

Voith Retarder Class B

Volvo VDS-4

GERMAN ADLER TX SYNT SAE 10W-40 Art.-N° **T003**

UPDATE

Contents

Description

- 5 I canister
- 20 I pail
- 60 I drum
- 200 I drum
- synthetic high performance/low friction oil
- for modern generations of diesel and gasoline motors
- excellent viscosity/temperature behavior
- high shear stability/support all season use
- stable lubrication film under extreme conditions/high temperature
- very low oil consumption
- very good oxidation stability

Specification / Recommendation

ACEA E7 API CI-4/CF/SL Caterpillar ECF-1a/ ECF-2

Cummins CES 20077 Cummins CES 20078

Deutz DQC III-18

DDC 93K215

Global DHD-1 Jaso DH-1

Mack EO-M Plus/EO-N MAN M 3275

MB 228.3

MTU Type 2 Renault RLD/RLD2

Volvo VDS-3



MOTOR OIL FOR COMMERCIAL VEHICLES

Art.-N° T028 GERMAN ADLER TX SYNT SAE 10W-40 HC-LA

UPDATE

Contents

5 | canister 20 | pail

60 l drum

200 l drum

Description

- synthetic ultra-high performance diesel motor oil (UHPD)
- for EURO 5 and EURO 6 commercial engines (2014 regulation by law)
- low sulphated ash sulphur and phosphorus content (low SAPS)
- for the trouble-free operating (particulate filter)
- high wear protection/reduces friction
- low evaporation tendency/good elastomer compatibility
- very high oxidation resistance
- protects against corrosion and black sludge
- reduces oil consumption
- excellent viscosity/temperature behavior
- high shear stability
- great fuel economy characteristics

Specification / Recommendation

ACEA E7/E8/E11 API CK-4 CAT ECF-3 Cummins CES 20086 DAF

DDC 93K222 Deutz DQC IV-18 LA Jaso DH-2

John Deere JDQ-78X Mack EO-S 4.5

MAN M 3477, M 3775, M 3575 MB MB 226.9/228.31/MB 228.51

MTU Typ 3.1 Renault VI RLD-3 Renault Truck RXD/RGD Scania LA Volvo CNG/VDS 4.5



Art.-N° **T004**

GERMAN ADLER TX SYNT SAE 10W-40 HC

UPDATE

Contents

5 I canister

20 I pail

60 l drum

200 l drum

Description

- synthetic ultra-high performance diesel motor oil (UHPD)
- for EURO 4 and EURO 5 commercial engines (2014 regulation by law)
- high wear protection/reduces friction
- very good cold start performance
- very high oxidation resistance
- protects against corrosion and black sludge
- reduces oil consumption
- excellent viscosity/temperature behavior
- high shear stability
- low evaporation tendency
- most extended oil drain intervals
- great fuel economy characteristics

Specification / Recommendation

ACEA E4/E7 API CI-4 + UHPD CAT ECF-1-a/ECF 2 Cummins CES 20076/ 20077/20078 DAF HP-2

Deutz DQC IV-10 Global DHD-1

IVECO

(if recommeded for E4-E7-08)

MACK EO-M+ MAN M 3277/M 3377 MB 228.5 MTU Type 3

Renault RXD/VI RLD-2

Scania LDF-3 Volvo VDS-3

Art.-N° **T143** GERMAN ADLER TX SYNT SAE 10W-30 CK-4

UPDATE

Contents

Description

5 I canister

- 20 I pail
- 60 I drum
- 200 I drum
- synthetic high-performance motor oil
- latest generation of low-emission engines
- low SAPS technology
- high shear stability followed by a stable lubrication film under extreme conditions at higher temperatures
- provides excellent fuel economy
- very good oxidation stability

Specification / Recommendation

ACEA E7/E11 API CK-4/CJ-4/SN API CI-4/CI-4 Plus CAT ECF-3 Cummins CES 20086 DAF PSQL 2.1E **Detroit Diesel** DFS93K222 Detroit Diesel DDC93K222 Deutz DQC-III-10LA/18LA Ford WSS-M2C171-F1 Jaso DH-2 Mack EOS-4.5

MAN M 3575/M 3775/M 3275 MB 228.31 MTU Type 2.1 Renault VI RLD-3 Volvo VDS-4.5

Art.-N° **T144** GERMAN ADLER TX SYNT SAE 10W-40 CK-4

UPDATE

Contents

Description

- 5 | canister
- 20 I pail
- 60 I drum
- 200 I drum
- synthetic high-performance motor oil
- latest generation of low-emission engines
- low SAPS technology
- high shear stability followed by a stable lubrication film under extreme conditions at higher temperatures
- provides excellent fuel economy
- very good oxidation stability

Specification / Recommendation

ACEA E7/E11 API CK-4/CJ-4/SN API CI-4/CI-4 Plus CAT ECF-3 Cummins CES 20086 **Detroit Diesel**

DFS93K222 **Detroit Diesel** DDC93K222

Deutz DQC-III-10LA/18LA Ford WSS-M2C171-F1

Jaso DH-2

John Deere JDQ-78X

Mack EOS-4.5

MAN M 3575/M 3775/M 3275

MB 228.31 MTU Type 2.1 Renault VI RLD-3 Volvo VDS-4.5



MOTOR OIL FOR COMMERCIAL VEHICLES

Art.-N° **T145 GERMAN ADLER** TX SAE 15W-40 CK-4

UPDATE

Contents

5 | canister

20 I pail

60 I drum

200 I drum

Description

- high-performance motor oil
- latest generation of low-emission engines
- low SAPS technology
- high shear stability followed by a stable lubrication film under extreme conditions at higher temperatures
- provides excellent fuel economy
- very good oxidation stability

Specification / Recommendation

ACEA E7/E11 API CK-4/CJ-4/SN API CI-4/CI-4 Plus Allison TES 439 CAT ECF-3 Cummins CES 20086 Detroit Diesel DFS93K222 Detroit Diesel DDC93K222 Deutz DQC-III-10LA/18LA Ford WSS-M2C171-F1 Jaso DH-2

Mack EOS-4.5 MAN M 3575/M 3775/M 3275 MB 228.31 MTU Type 2.1 Renault VI RLD-3 Volvo VDS-4.5

John Deere JDQ-78X

GERMAN ADLER TX SAE 15W-40 Art.-N° **T041**

Contents

5 | canister

20 I pail

60 I drum

200 I drum

Description

- super high performance diesel (SHPD) motor oil
- multifunctional for diesel and gasoline engines also with turbocharger
- made for passenger cars, trucks, busses, farm and off road equipment
- meets specifications of European, American and Japanese manufacturers
- excellent thermal/oxidative stability
- reduces sludge and deposit built-up
- maximum oil drain intervals due to highest TBN reserves
- best seal and elastomer compatibility
- slow oil ageing even at high temperatures
- all season oil for mixed fleets

Specification / Recommendation

ACEA E7 API CI-4/SL CAT ECF-1/ECF-2 **Cummins CES** 20077/-78 DDC 93K215 Deutz DQC III-10 GLOBAL DHD-1 JASO DH-1 Mack EO-M Plus/EO-N MAN M 3275 MB 228.3 MTU Typ 2.0

Renault RLD1/RLD2 Volvo VDS-3



GERMAN ADLER TX SAE 20W-50 PLUS Art.-N° **T130**

Contents

5 I canister

20 I pail 60 I drum

200 I drum

Description

- super high performance diesel (SHPD) motor oil
- multifunctional for diesel and gasoline engines also with turbocharger
- made for passenger cars, trucks, busses, farm and off road equipment
- meets specifications of European, American and Japanese manufacturers
- excellent thermal/oxidative stability
- reduces sludge and deposit built-up
- maximum oil drain intervals due to highest TBN reserves
- best seal and elastomer compatibility
- slow oil ageing even at high temperatures
- all season oil for mixed fleets

Specification / Recommendation

ACEA E7-10 ACEA A3-/B4-10 API CI-4/SL Allison C-4 CAT ECF-1-a/ECF-2 Cummins CES 20071/-75/-76/ -77/-78 DEUTZ DQC III-10 Fiat 9.55535-G2/D2 **GLOBAL DHD-1** JASO DH-1 Mack EO-M PLUS MAN M 3275 MB 228.3/229.1 MTU Type 2

Renault RLD-2 Volvo VDS-3





Art.-N° **A027 GERMAN ADLER AGRA SAE 10W-30**

Contents

20 I pail 60 I drum 200 I drum

Description

- multigrade Super-Tractor-Oil-Universal (STOU)
- universal, all season oil for all types of agricultural
- for engines, gears, hydraulics and brake systems (wet brakes)
- excellent operation for engines, gears, axes, differentials, hydraulic and brake systems
- very good protection against corrosion/black sludge
- high wear protection at full engine load
- low foaming tendency

Specification / Recommendation

API CF/CG-4/SF API GL-4 Allison C-4 Case NH MAT 3525/3526 Caterpillar TO-2 HVLP-D accord. DIN 51 524 part 3 Ford M2C159B/C John Deere JDM 27 Massey Ferguson M 1139/1144/1145 MB 227.1/228.1 ZF TE-ML-06A/-06B/-06C/-07B



GERMAN ADLER AGRA SAE 10W-40 Art.-N° **A055**

Contents

20 I pail 60 I drum 200 l drum

Description

- synthetic Super-Tractor-Oil-Universal (STOU)
- universal, all season oil for all types of agricultural machines
- for engines, gears, hydraulics and brake systems (wet brakes)
- excellent operation for engines, gears, axes, differentials, hydraulic and brake systems
- very good protection against corrosion/black sludge
- high wear protection at full engine load
- low foaming tendency

Specification / Recommendation

ACEA E3 API CG-4 API GL-4 HVLP-D accord. DIN 51 524 part 3 (for 10W40) Allison C-4 Case M5/1118/1207/ 1209/MAT3525/CS/

CVX Claas Renault

Agriculture Harvester B6 Fendt Vario

Ford M2C 159B/C, M2C 86B/C,

M2C 134D

John Deere JDM/J20C/J27 Landini/Lindner/Mc-Cormick Massey Ferguson M1135 to 1145 New Holland NH 410B/420A/526C Same-Deutz-Lamborghini-Hirlimann T3245/3340/3345/3445/3450/3550 Valmet

ZF TE-ML-06B (inc.06R), -06C, -07B Steyr Serie 900/9000/CVT

Art.-N° **A014 GERMAN ADLER AGRA SAE 15W-30**

Contents

Description

20 I pail 60 I drum 200 I drum

- Super High Performance Diesel (SHPD) motor oil
- multi functional for diesel and gasoline engines also turbochargers
- made for passenger, trucks, busses, farm and off road equipment
- meets specifications of European, American and Japanese manufacturers
- excellent thermal/oxidative stabilityreduces sludge built-up und deposits
- maximum oil drain intervals by highest TBN reserve
- best seal and elastomer compatibility
- reduces oil ageing even at high temperatures
- all season oil for mixed fleet

Specification / Recommendation

API CF/CG-4/SF API GL-4 ACEA E3-96 Allison C-4 Case NH MAT 3525/3526 Caterpillar TO-2 Ford M2C159B/C HVLP-D 68 accord. DIN 51 524 part 3 (for 15W30) HVLP-D 100 accord. DIN 51 524 part 3 (for 15W40) John Deere JDM 27 Massey Ferguson M 1139/1144/1145 MB 227.1/228.1

Art.-N° **A013 GERMAN ADLER UTTO SAE 10W-30**

Contents

Description

20 I pail 60 I drum


200 I drum

- Universal Tractor Transmission Oil (UTTO)
- for gears, hydraulics and wet breaks
- very good anti wear and anti corrosion properties
- excellent oxidation stability
- extended oil drain intervals
- high shaer stability

Specification / Recommendation

ZF TE-ML-06A/-06B/-06C/-07B

API GL-4 Allison C-4/C-3 Case MS 1204, 1205, 1206, 1207, 1209, 1210 Caterpillar TO-2 Deutz Hydr Trans Fluid Ford M2C 34D Ford M2C 6A-C John Deere J-20C/D



ZF TE-ML-03E/-06



GERMAN ADLER SAE 30 TO-4 Art.-N° **A017**

Contents

Description

20 I pail 60 l drum 200 I drum

- high performance transmission fluid
- excellent corrosion protection for steel and non-ferrous metals
- good cold flow properties
- low friction
- high elastomer compatibility

Specification / Recommendation

API GL-4 API CF Allison C-4, TES-439 Caterpillar TO-4 Komatsu ZF TE-ML 03C, 07F



Art.-N° **A023 GERMAN ADLER SAE 50 TO-4**

Contents

20 I pail 60 I drum

200 I drum

Description

- high performance transmission fluid
- excellent corrosion protection for steel and non-ferrous metals
- good cold flow propertieslow friction
- high elastomer compatibility

Specification / Recommendation

API GL-4 API CF Caterpillar TO-4 Komatsu



MONO-GRADE MOTOR OILS

Art.-N° **M015 GERMAN ADLER SAE 10 HD**

Contents

Description

- 1 l bottle
- 4 | canister
- 5 I canister
- 20 I pail
- 60 I drum
- 200 I drum
- mono grade motor oil
- mineral base oils and selected additives
- excellent for turbocharged engines
- high TBN/improved neutralization capacity
- stable lubrication film
- very good detergency and dispersancy
- provides excellent motor cleanliness
- corrosion and wear protection
- oxidation protection

Specification / Recommendation

API SF/CF/CF-4



GERMAN ADLER SAE 30 HD Art.-N° **M022**

Contents

1 l bottle

- 4 | canister
- 5 I canister
- 20 I pail
- 60 I drum
- 200 I drum

Description

- mono grade motor oil
- mineral base oils and selected additives
- excellent for turbocharged engines
- high TBN/improved neutralization capacity
- stable lubrication film
- very good detergency and dispersancy
- provides excellent motor cleanliness
- corrosion and wear protection
- oxidation protection

Specification / Recommendation

API SF/CF/CF-4



GERMAN ADLER SAE 40 HD Art.-N° **M012**

Contents

Description

- 1 | bottle
- 4 | canister
- 5 I canister 20 I pail
- 60 l drum
- 200 I drum
- mono grade motor oil
- mineral base oils and selected additives
- excellent for turbocharged engines
- high TBN/improved neutralization capacity - stable lubrication film
- very good detergency and dispersancy
- provides excellent motor cleanliness
- corrosion and wear protection
- oxidation protection

Specification / Recommendation

API SF/CF/CF-4



GERMAN ADLER SAE 50 HD Art.-N° **M040**

Contents

1 l bottle

- 4 | canister
- 5 I canister
- 20 l pail 60 l drum
- 200 I drum

Description

- mono grade motor oil
- mineral base oils and selected additives
- excellent for turbocharged engines
- high TBN/improved neutralization capacity
- stable lubrication film
- very good detergency and dispersancy
- provides excellent motor cleanliness
- corrosion and wear protection
- oxidation protection



Specification / Recommendation

API SF/CF/CF-4

Art.-N° **M016 GERMAN ADLER SAE 60 HD**

Contents

1 l bottle

- 4 | canister
- 5 I canister
- 20 I pail
- 60 I drum
- 200 I drum

Description

- mono grade motor oil
- mineral base oils and selected additives
- for normal aspired engines and also suitable for turbocharged engines
- high TBN/improved neutralization capacity
- stable lubrication film
- good detergency and dispersancy
- provides motor cleanliness
- corrosion and wear protection as well as
- oxidation protection

Specification / Recommendation

API SF/CF



Art.-N° **M110 GERMAN ADLER SAE 40 CI-4**

Contents

- 1 l bottle
- 4 | canister
- 5 I canister
- 20 I pail
- 60 I drum
- 200 I drum

Description

- mono grade motor oil
- mineral base oils and selected additives
- excellent for turbocharged engines
- high TBN/improved neutralization capacity
- stable lubrication film
- very good detergency and dispersancy
- provides excellent motor cleanliness
- corrosion and wear protection
- oxidation protection

Specification / Recommendation

API CI-4/SL



Art.-N° **M115 GERMAN ADLER SAE 50 CI-4**

Contents

1 l bottle

- 4 | canister
- 5 I canister
- 20 I pail
- 60 I drum
- 200 I drum

Description

- mono grade motor oil
- mineral base oils and selected additives - excellent for turbocharged engines
- high TBN/improved neutralization capacity
- stable lubrication film
- very good detergency and dispersancy
- provides excellent motor cleanliness
- corrosion and wear protection
- oxidation protection

Specification / Recommendation

API CI-4/SL



GERMAN ADLER SAE 10 GST Art.-N° **M021**

Contents

- 1 l bottle
- 4 | canister
- 5 I canister
- 200 I drum

20 l pail 60 l drum

Description

- mono grade motor oil
- for gasoline and diesel engines
- protects against black sludge
- protects against thermal oxidation, corrosion and wear
- all season oil

Specification / Recommendation

API SF/CD DIN 51 506





Art.-N° **M052 GERMAN ADLER SAE 30 GST**

Contents

Description

1 l bottle

- 4 | canister 5 I canister
- 20 I pail
- 60 I drum
- 200 I drum
- mono grade motor oil
- for gasoline and diesel engines
- protects against black sludge
- protects against thermal oxidation, corrosion and wear
- all season oil

Specification / Recommendation

API SF/CD DIN 51 506



GERMAN ADLER SAE 40 GST Art.-N° **M047**

Contents

- 1 l bottle
- 4 | canister
- 5 I canister
- 20 I pail
- 60 I drum
- 200 I drum

Description

- mono grade motor oil
- for gasoline and diesel engines
- protects against black sludge
- protects against thermal oxidation, corrosion and wear
- all season oil

Specification / Recommendation

API SF/CD DIN 51 506 (not to use in compressors where the manufacturer requires zinc free product)



GERMAN ADLER SAE 50 GST Art.-N° **M091**

Contents

1 | bottle

- 4 | canister
- 5 I canister
- 20 I pail 60 I drum
- 200 I drum

Description

- mono grade motor oil
- for gasoline and diesel engines
- protects against black sludge
- protects against thermal oxidation, corrosion and wear
- all season oil

Specification / Recommendation

API SF/CD DIN 51 506 (not to use in compressors where the manufacturer requires zinc free product)



GERMAN ADLER SAE 20W-20 GST Art.-N° **M023**

Contents

1 | bottle

4 | canister

5 I canister

20 l pail 60 l drum

200 I drum

Description

- mono grade motor oil
- for gasoline and diesel engines
- protects against black sludge
- protects against thermal oxidation, corrosion and wear
- all season oil

Specification / Recommendation

API SF/CD DIN 51 506



Art.-N° **Z032 GERMAN ADLER 2T-F**

Contents

Description

- 1 l bottle
- 4 I canister
- 5 I canister
- 20 I pail
- 60 l drum
- 200 I drum
- Description
- fully synthetic high performance oil
- suitable for air and water cooled racing engines
- meets most specification requirements of all two-stroke motor manufacturers
- latest additive technology/low ash
- optimal motor lubrication even under high-speed racing conditions
- improved pollution control by scentless and smokeless combustion

Specification / Recommendation

API TC ISO-L-EGD JASO FD



Art.-N° **Z030 GERMAN ADLER 2T-S**

Contents

- 1 | bottle
- 4 l canister
- 5 I canister
- 20 I pail
- 60 I drum
- 200 l drum

Description

- synthetic high performance two-stroke oil
- can be used universally in two-stroke engines
- pressure resistant oil film at all lubrication points
- excellent anti corrosion, anti oxidation and anti wear behavior
- excellent high temperture performance/no smoke

Specification / Recommendation

API TC ISO-L-EGD JASO FD



Art.-N° **Z031 GERMAN ADLER 2T-M**

Contents

- 1 | bottle
- 4 | canister
- 5 I canister
- 20 I pail
- 60 l drum
- 200 l drum

Description

- two-stroke motor oil for mixture and separate lubrication
- based on mineral oil and applicable for two-stroke
- protects the engine against corrosion and wear
- is self-mixing and forms a homogeneous mixture with the fuel

Specification / Recommendation

API TC ISO-L-EGC JASO FC



Art.-N° Z049 GERMAN ADLER 4T-S 10W-40

UPDATE

Contents 1 | bottle

4 I canister

5 I canister

20 I pail

200 l drum

60 I drum

Description

high performance multigrade oil for motorcycles

- especially for motorcycles with air and water cooled four-stroke engines of highest output
- ideal partner for all sportive motorcycles
- optimal lubrication in motor and in gear
- excellent motor cleanliness especially at pistons and valves

Specification / Recommendation

ACEA A3-04 API SN Plus JASO MA2



Art.-N° **Z050**

GERMAN ADLER 4T-M 20W-50

Contents

1 l bottle

- 4 I canister
- 5 I canister
- 20 l pail
- 200 l drum

60 l drum

Description

- high performance multigrade oil for motorcycles
- especially for motorcycles with air and water cooled four stroke engines of highest output
- ideal partner for all sportive motorcyles
- optimal lubrication in motor and in gear
- excellent motor cleanliness especially at pistons and valves

Specification / Recommendation

ACEA A3-04 API SN JASO MA2







ERMARI DIEE

Art.-N° **G011 GERMAN ADLER ATF 4-0 R**

Contents

1 l bottle

4 I canister

5 I canister

20 I pail

60 I drum

200 I drum

Description

- automatic transmission fluid
- usable in passenger and commercial cars, other vehicles and aggregates

- for power steering systems, automatic and manual transmissions power shift gear, hydraulic systems
- very good friction stability
- excellent low and high temperature shifting performance
- good anti-wear properties/maximum lifetime
- very good ageing and oxidation stability
- reduced foaming tendency
- prevents from corrosion, wear and deposits
- good sealing compatibility

Specification / Recommendation

GM DEXRON IID GM DEXRON III Allison C3/C4 Caterpillar TO-2 Ford SQM-9010B Ford M2C-38CJ, 166H, 185A MAN 339 Typ D MB 236.7 Voith ZF TE-ML 03D, 04D, 09A, 11A, 14A



Art.-N° **G021**

GERMAN ADLER ATF 4-0 F

Contents

- 1 | bottle 4 I canister
- 5 I canister
- 20 I pail
- 60 I drum
- 200 I drum

Description

- automatic transmission fluid
- usable in passenger and commercial cars,

other vehicles and aggregates

- for power steering systems, automatic and manual transmissions power shift gear, hydraulic systems
- very good friction stability
- excellent low and high temperature shifting performance
- good anti-wear properties/maximum lifetime
- very good ageing and oxidation stability
- reduced foaming tendency
- prevents from corrosion, wear and deposits
- good sealing compatibility

Specification / Recommendation

GM DEXRON IID GM DEXRON III Allison C3/C4 Caterpillar TO-2 Ford SQM-9010B Ford M2C-38CJ, 166H, 185A MAN 339 Typ D MB 236.7 Voith ZF TE-ML 03D, 04D, 09A, 11A, 14A



Art.-N° **G020 GERMAN ADLER ATF 9-0 R**

Contents

- 1 l bottle
- 4 | canister
- 5 I canister
- 20 I pail
- 60 I drum
- 200 I drum

Description

- synthetic automatic transmission fluid
- automatic transmission fluid for passenger cars and heavy duty vehicles
- meets the requirements of most current specifications of American, European and Asian manufacturers
- prevents from miss disposition
- smart ware housing
- excellent low-temperature shifting performance
- long-term friction stability
- best anti-wear properties/maximum lifetime
- outstanding ageing and oxidation stability
- reduced foaming tendency
- prevents reliably from corrosion, wear and deposits
- good sealing compatibility

Specification / Recommendation

DEXRON IIIH DEXRON IIIG **DEXRON IIE DEXRON IID** Allison C-4 Allison TES, 389 CAT TO-2 Ford Mercon Ford M2C138-CJ, M2C 166-H MB 236.1/236.5/ 236.6/236.7/236.9 MAN 339 Typ Z1/V1, Z2/V2

TASA Volvo 97340, 97341

Voith 55.6335 / 55.6336 ZF TE-ML 02F, 03D, 04D, 09, 11A, 11B, 14A, 17C

GERMAN ADLER ATF 9-0 F Art.-N° **G026**

Contents

- 1 l bottle
- 4 | canister
- 5 L canister
- 20 I pail
- 60 I drum 200 I drum

Description

- synthetic automatic transmission fluid
- automatic transmission fluid for passenger cars and heavy duty vehicles
- meets the requirements of most current specifications of American, European and Asian manufacturers
- prevents from miss disposition
- smart ware housing
- excellent low-temperature shifting performance
- long-term friction stability
- best anti-wear properties/maximum lifetime
- outstanding ageing and oxidation stability
- reduced foaming tendency
- prevents reliably from corrosion, wear and deposits
- good sealing compatibility

Specification / Recommendation

ATF 9-0 F

DEXRON IIIH DEXRON IIIG DEXRON IIE DEXRON IID Allison C-4 Allison TES, 389 CAT TO-2 Ford Mercon Ford M2C138-CJ, M2C 166-H MB 236.1/236.5/ 236.6/236.7/236.9 MAN 339 Typ Z1/V1, Z2/V2 TASA Volvo 97340, 97341

AUTOMATIC TRANSMISSION FLUIDS (ATF)

Art.-N° G081 GERMAN ADLER ATF 9-1 R

UPDATE

Specification / Recommendation

Contents 1 | bottle

20 I pail

60 I drum

200 I drum

Description

- synthetic automatic transmission fluid

4 l canister - meets major Asian (Japanese & Korean) 5 l canister OEM specifications

- smooth gear shift

- fuel economical

- excellent anti-corrosion and anti-wear properties for gearboxes



Specification / Recommendation

GM DEXRON II/IIC/IID/IIE/IIIG/IIIH/B/IIIF; Allison C-2, C-3, C-4, TES-295, TES-389; Aisin Warner JWS 3309; ATF 3100 PL085/3403-M115/ETL-7045 E/K17/LA 2634/N402; BMW ATF 4; BMW ETL 7045/7045E/8072/ N402/ LA 2634/LT 71141; BMW P/N 83 22 2 220 438/440; BMW P/N 83 22 2 220 442; BMW/Mini P/N 81 22 9 400 272/275; BMW/Mini P/N 81 22 9 407 858/859; BMW/Mini P/N 83 22 0 024 249/359; BMW/Mini P/N 83 22 0 026 922 (BMW 7045 E); BMW/Mini P/N 83 22 0 402 413; BMW/Mini P/N 83 22 0 403 248/249; BMW/Mini P/N 83 22 7 542 290; BMW/Mini P/N 83 22 9 407 765 (BMW LA 2634); BMW/Mini P/N 83 22 9 407 807 (LT 71141); Bosch TE-ML 09; Daihatsu D3-SP; Daimler Mercedes MB 236.1/236.2/236.5/236.6/236.7/236.8/236.9; Daimler Mercedes MB 236.10/236.11/236.12/236.14/236.91; Fiat Chrysler ASRC, ATF+/ATF+2/ATF+3/ATF +4; Fiat Chrysler MB 236.10/12, P/N 05127382AA; Fiat Chrysler P/N 68333587AA; Fiat Chrysler SP-III; Fiat Chrysler Type 7176E; Fiat Chrysler Type 9602; Ford ESP-M2C138-CJ; Ford ESP-M2C166-H; FORD WSS-M2C919-E (Mercon V); FORD/Lincoln/Mercury P/N XT-2-QDX [M]; FORD/Lincoln/Mercury P/N XT-2-QSM [Syn]; FORD/Lincoln/Mercury P/N XT-5-QM or -DM [V]; FORD/Lincoln/Mercury P/N XT-8-QAW [Premium]; FORD/Lincoln/Mercury P/N XT-9-QMM5 [FNR5]; FORD/Lincoln/Mercury WSS-M2C922-A1; FORD XT-5-QMC (Mercon V); FORD XT-5-QSM (V Syn); GM/GMC/Opel/Saturn ATF Z1, P/N 22717466; GM/GMC/Opel/Saturn P/N 19 40 700/767; GM/GMC/Opel/ Saturn P/N 21005966 (transaxle); GM/GMC/Opel/Saturn P/N 88900925/9986195; GM/GMC/Opel/Saturn P/N 9985010; GM/GMC/Opel/Saturn T-IV, Type A Suffix A; Honda/Acura Z-1 (P/N 08200-9001 & 08200-9001A); Honda ATF DPSF-II; Hyundai/Kia ATF Red-1K; Hyundai/Kia Genuine ATF; Hyundai/Kia JWS 3314; Hyundai/Kia JWS-3309 T4; Hyundai/Kia P/N 00232-19023; Hyundai/Kia P/N 04500-00140; Hyundai/Kia P/N 04500-00 U M040 CH-020 Red-1; Idemitsu ATF HP; Idemitsu K17; Isuzu P/N 08200-9001; Isuzu ATF II/III; Isuzu Genuine ATF; Jaso M315, Class 1A, 1A-02; Jaguar JLM 20238/20292/21044/K17; Jaguar WSS-M2C922-A1; Jaguar LT 71141; Land Rover Texaco ETL-7045E; Land Rover ATF N402; Land Rover JWS3309US; MAN 339 A, D, F; Mazda ATF M-5, N-1, S-1; Mazda F-1; Mazda M3; Mazda F-1, JWS 3317; Mazda M-5, P/N XT-9-QMM5; Mazda M-III, Type T-IV; Mercon V; Mitsubishi ATF-J2; Mitsubishi Dia Queen AW; Mitsubishi DII/ DIII; Mitsubishi SP, P/N MS991156; Mitsubishi SP-II/III; Mobil ATF 3309; Mercedes A 0019892203; Mercedes ATF 3403 -M115; Nissan/Infinity 402; Nissan/Infinity Fluid A; Nissan/Infinity Matic-D/J/K/W; Porsche P/N 000 043 204 41; Porsche P/N 000 043 204 63; Porsche P/N 000 043 205 09; Porsche P/N 000 043 205 28; Porsche P/N 999 917 547 00 (A2); Porsche LT 71141; Peugeot P/N Z 000169756; PSA AL4 / 4HP20, P/N 9730AE; PSA B71 2340; PSA Peugeot Citroen P/N Z 000169756; Renault DP-0, Matic D2, SATF-D; Rolls Royce Oil No. PL 31493PA; Renk Genuine Oil; Saab ATF HP; Saab P/N 93 160 393; Saab 3309 - T-IV; Saturn Dex- IIIG, T-IV Fluid, P/N 22689186; Shell 3403-M115, LA 2634; SSANG YONG DSIH 5M-52, 5M-66; Subaru HP; Subaru P/N K0140Y0700; Suzuki 2326/2384K/3314/3317/5D06; Suzuki Matic D/J; Toyota/Lexus/Scion Type D-II/T/T-II/T-III/T-IV; Toyota JWS 3309/3324; VW/Audi LT 71141; VW/Audi G 052 025 A, G 052 055; VW/Audi G 052 162 (A1, A2); VW/Audi G 052 990 (A2), G 055 025 (A2); VW/Audi US 000 162; Voith H55.6335.XX; Voith Svc Bltn # 013 /118; Volvo P/N 1161521/1161621; Volvo P/N 1161540 /1161640; Volvo P/N 1273,41; 97340, 97341; ZF TE-ML 05L /11A/11B/21L; ZF 6 Speed (S671 ZF LifeguardFluid 5 (ZF No. S671 090 170)

Art.-N° **G091 GERMAN ADLER ATF 9-1 F**

UPDATE

Contents

Description

Specification / Recommendation

- 1 l bottle
- synthetic automatic transmission fluid
- 4 | canister
- 5 I canister
- 20 I pail
- 60 I drum 200 I drum
- meets major Asian (Japanese & Korean) OEM specifications
- smooth gear shift
- fuel economical
- excellent anti-corrosion and anti-wear properties for gearboxes



Specification / Recommendation

GM DEXRON II/IIC/IID/IIE/IIIG/IIIH/B/IIIF; Allison C-2, C-3, C-4, TES-295, TES-389; Aisin Warner JWS 3309; ATF 3100 PL085/3403-M115/ETL-7045 E/K17/LA 2634/N402; BMW ATF 4; BMW ETL 7045/7045E/8072/ N402/ LA 2634/LT 71141; BMW P/N 83 22 2 220 438/440; BMW P/N 83 22 2 220 442; BMW/Mini P/N 81 22 9 400 272/275; BMW/Mini P/N 81 22 9 407 858/859; BMW/Mini P/N 83 22 0 024 249/359; BMW/Mini P/N 83 22 0 026 922 (BMW 7045 E); BMW/Mini P/N 83 22 0 402 413; BMW/Mini P/N 83 22 0 403 248/249; BMW/Mini P/N 83 22 7 542 290; BMW/Mini P/N 83 22 9 407 765 (BMW LA 2634); BMW/Mini P/N 83 22 9 407 807 (LT 71141); Bosch TE-ML 09; Daihatsu D3-SP; Daimler Mercedes MB 236.1/236.2/236.5/236.6/236.7/236.8/236.9; Daimler Mercedes MB 236.10/236.11/236.12/236.14/236.91; Fiat Chrysler ASRC, ATF+/ATF+2/ATF+3/ATF+4; Fiat Chrysler ASRC, ATF+/ATF+2/ATF+3/ATF+4; Fiat Chrysler ASRC, ATF+ATF+3/ATF+4; Fiat Chrysler ASRC, ATF+ATF+3/ATF+3/ATF+4; Fiat Chrysler ASRC, ATF+ATF+3/ATF+3/ATF+4MB 236.10/12, P/N 05127382AA; Fiat Chrysler P/N 68333587AA; Fiat Chrysler SP-III; Fiat Chrysler Type 7176E; Fiat Chrysler Type 9602; Ford ESP-M2C138-CJ; Ford ESP-M2C166-H; FORD WSS-M2C919-E (Mercon V); FORD/Lincoln/Mercury P/N XT-2-QDX [M]; FORD/Lincoln/Mercury P/N XT-2-QSM [Syn]; FORD/Lincoln/Mercury P/N XT-5-QM or -DM [V]; FORD/Lincoln/Mercury P/N XT-8-QAW [Premium]; FORD/Lincoln/Mercury P/N XT-9-QMM5 [FNR5]; FORD/Lincoln/Mercury WSS-M2C922-A1; FORD XT-5-QMC (Mercon V); FORD XT-5-QSM (V Syn); GM/GMC/Opel/Saturn ATF Z1, P/N 22717466; GM/GMC/Opel/Saturn P/N 19 40 700/767; GM/GMC/Opel/Saturn P/N 21005966 (transaxle); GM/GMC/Opel/Saturn P/N 88900925/9986195; GM/GMC/Opel/Saturn P/N 9985010; GM/GMC/Opel/Saturn T-IV, Type A Suffix A; Honda/Acura Z-1 (P/N 08200-9001 & 08200-9001A); Honda ATF DPSF-II; Hyundai/Kia ATF Red-1K; Hyundai/Kia Genuine ATF; Hyundai/Kia JWS 3314; Hyundai/Kia JWS-3309 T4; Hyundai/Kia P/N 00232-19023; Hyundai/Kia P/N 04500-00140; Hyundai/Kia SP/SP-II/III; Hyundai/Kia P/N U M040 CH-020 Red-1; Idemitsu ATF HP; Idemitsu K17; Isuzu P/N 08200-9001; Isuzu ATF II/III; Isuzu Genuine ATF; Jaso M315, Class 1A, 1A-02; Jaguar JLM 20238/20292/21044/K17; Jaguar WSS-M2C922-A1; Jaguar LT 71141; Land Rover Texaco ETL-7045E; Land Rover ATF N402; Land Rover JWS3309US; MAN 339 A, D, F; Mazda ATF M-5, N-1, S-1; Mazda F-1; Mazda M3; Mazda F-1, JWS 3317; Mazda M-5, P/N XT-9-QMM5; Mazda M-III, Type T-IV; Mercon V; Mitsubishi ATF-J2; Mitsubishi Dia Queen AW; Mitsubishi DII/ DIII; Mitsubishi SP, P/N MS991156; Mitsubishi SP-II/III; Mobil ATF 3309; Mercedes A 0019892203; Mercedes ATF 3403 -M115; Nissan/Infinity 402; Nissan/Infinity Fluid A; Nissan/Infinity Matic-D/J/K/W; Porsche P/N 000 043 204 41; Porsche P/N 000 043 204 63; Porsche P/N 000 043 205 09; Porsche P/N 000 043 205 28; Porsche P/N 999 917 547 00 (A2); Porsche LT 71141; Peugeot P/N Z 000169756; PSA AL4 / 4HP20, P/N 9730AE; PSA B71 2340; PSA Peugeot Citroen P/N Z 000169756; Renault DP-0, Matic D2, SATF-D; Rolls Royce Oil No. PL 31493PA; Renk Genuine Oil; Saab ATF HP; Saab P/N 93 160 393; Saab 3309 - T-IV; Saturn Dex- IIIG, T-IV Fluid, P/N 22689186; Shell 3403-M115, LA 2634; SSANG YONG DSIH 5M-52, 5M-66; Subaru HP; Subaru P/N K0140Y0700; Suzuki 2326/2384K/3314/3317/5D06; Suzuki Matic D/J; Toyota/Lexus/Scion Type D-II/T/T-II/T-III/T-IV; Toyota JWS 3309/3324; VW/Audi LT 71141; VW/Audi G 052 025 A, G 052 055; VW/Audi G 052 162 (A1, A2); VW/Audi G 052 990 (A2), G 055 025 (A2); VW/Audi US 000 162; Voith H55.6335.XX; Voith Svc Bltn # 013 /118; Volvo P/N 1161521/1161621; Volvo P/N 1161540 /1161640; Volvo P/N 1273,41; ZF 97340, 97341; TE-ML 05L /11A/11B/21L; ZF 6 Speed ZF LifeguardFluid 5 (ZF No. S671 090 170)

AUTOMATIC TRANSMISSION FLUIDS (ATF)

Art.-N° G050 GERMAN ADLER ATF 9-4 R

Contents

- 1 l bottle
- 4 | canister
- 5 I canister
- 20 I pail
- 60 l drum
- 200 l drum

Description

- synthetic lifetime automatic transmissions fluid
- especially made for Mercedes Benz
- extremely shear stable VI-improver
- modern anti-wear additives and balanced friction modifiers
- excellent gear changing properties

Specification / Recommendation

MB 236.12 MB 236.14 Audi/VW G 052 162 (A1, A2) Jaguar JLM 20238 Porsche P/N 999 917 547 00 PSA Peugeot/Citroen P/N Z 000169756



Art.-N° G051 GERMAN ADLER ATF 9-4 F

Contents

- 1 | bottle
- 4 | canister
- 5 I canister
- 3 i carriste
- 20 | pail
- 200 l drum
- 60 l drum

Description

- synthetic lifetime automatic transmission fluid
- particulary made for Mercedes Benz
- extremely shear stable VI-improver
- modern anti-wear additives and balanced friction modifiers
- smooth gear shifting properties

Specification / Recommendation

MB 236.12 MB 236.14 Audi/VW G 052 162 (A1, A2) Jaguar JLM 20238 Porsche P/N 999 917 547 00 PSA Peugeot/Citroen P/N Z 000169756



Art.-N° G060 GERMAN ADLER ATF 9-5 B

Contents

- 1 l bottle
- 4 | canister
- 5 I canister
- 20 l pail 60 l drum
- 200 l drum

Description

- synthetic automatic transmission fluid especially developed for Mercedes-Benz-7-speed automatic transmission
- extremely shear stable with modern anti-wear additives
- reduced viscosity for maximum fuel efficiency
- adapted friction coefficient behaviour for smooth shifting operations
- best wear protection properties for reliable operation and the longest service life
- outstanding oxidation and thermal stability
- neutral to metals and sealing materials

Specification / Recommendation

MB 236.15





AUTOMATIC TRANSMISSION FLUIDS (ATF)

Art.-N° **G037 GERMAN ADLER ATF 9-6 LV F**

UPDATE

ATF9-6LV

Contents


- 1 l bottle
- 4 | canister
- 5 I canister
- 20 I pail
- 60 I drum
- 200 I drum

Description

- synthetic automatic transmission fluid
- optimized for passenger car applications
- for an extensive range of European and Asian passenger cars
- can be used in commercial vehicle applications and power steerings
- exceptional oxidation behaviour
- anti-shudder durability
- smoother shifts over a long period of time
- excellent anti-rust properties
- low foaming tendency
- good sludge and vanish control

Specification / Recommendation

DEXRON VI Aisin Warner AW-1, AW F8FXX, JWS 3324, ATF-0WS; ATF 134 / 3353 L12108 / M-1375.4; ATF M-1375.6 / Shell 3403-M115; Bentley P/N PY112995PA; BMW ATF 3+, ATF 6 BMW M-L12108;



P/N 83 22 0 397 114, P/N 83 22 2 163 514 (BMW 8072 B), P/N 83 22 2 152 426,

P/N 83 22 2 289 720, P/N 83 22 2 305 396 (ATF 2), P/N 83 22 2 305 397, P/N 83 22 2 355 599,

P/N 83 22 2 355 601; Chrysler/Dodge/Jeep

P/N 05127382AA, P/N 68043742AA;

Daimler/Mercedes

MB 236.12, 236.14, 236.41; FIAT 9.55550-AV1;

Fiat Chrysler 8&9 Speed ATF, AW-1, Dex-VI, P/N 05127382, P/N 68157995AA/AB, SP-4,

P/N 68171866AA, SP-IV, P/N 68171866AA, SP-IV, P/N 68171869AA;

FORD/Lincoln/Mercury P/N XT-10-QLV [LV], P/N XT-6-QSP or -DSP, Spec WSS-M2C922-A1;

GM Dex HP; GM/GMC/Opel/Saturn AW1,

P/N 88863400;

Honda/Acura DW-1, ATF Type 3.0; Honda 082000-9017 (ATF Type 3.1); Hyundai/Kia NWS-9638 T-5, WS, spec NWS-9638; P/N 040000C90SG, SP4-M1 / SP-IV / SP-IV-RR, SPH-VI;

Isuzu SCS; Jaguar 02JDE 26444 / Fluid 8432; JASO M315, Class 1A-LV;

Jeep ATF LGF8;

Land Rover P/N TYK500050, LR0022460-AW-1, P/N LR0022460: LV,

LR023288/023289 Maserati P/N 231603;

Mazda FW 6A EL, FW 6AX EL, FZ;

Mercon LV;

Mitsubishi ATF-J3, SP-IV, Dia Queen ATF-MA1, Dia Queen ATF-PA;

Nissan/Infinity Matic-S / Matic-W; Porsche P/N 000 043 304 00; Saab P/N 93 165 147 - AW-1;

Shell 3353/134/1375.4; Subaru WŚ;

Suzuki Matic S;

Toyota/Lexus/Scion WS; Volvo P/N 31 256 774, 31 256 775; VW/Audi G 052 533, G 055 005 (-A, A2),

G 055 540 (A2), G 055 162 A2 or A6, G 060 162 A2;

ZF Lifequard 6/8/9

Art.-N° **G047 GERMAN ADLER ATF 9-6 LV R**

UPDATE

Contents

- 1 l bottle
- 4 | canister
- 5 I canister
- 20 I pail
- 60 I drum
- 200 I drum

Description

- synthetic automatic transmission fluid
- optimized for passenger car applications
- for an extensive range of European and Asian passenger cars
- can be used in commercial vehicle applications and power steerings
- exceptional oxidation behaviour
- anti-shudder durability
- smoother shifts over a long period of time
- excellent anti-rust properties
- low foaming tendency
- good sludge and vanish control

Specification / Recommendation

DEXRON VI Aisin Warner AW-1, AW F8FXX, JWS 3324, ATF-0WS; ATF 134 / 3353 L12108 / M-1375.4; ATF M-1375.6 / Shell 3403-M115; Bentley P/N PY112995PA; BMW ATF 3+, ATF 6 BMW M-L12108; BMW/Mini P/N 83 22 0 142 516, P/N 83 22 0 397 114, P/N 83 22 2 163 514 (BMW 8072 B), P/N 83 22 2 152 426, P/N 83 22 2 289 720, P/N 83 22 2 305 396 (ATF 2), P/N 83 22 2 305 397, P/N 83 22 2 355 599 P/N 83 22 2 355 601; Chrysler/Dodge/Jeep P/N 05127382AA, P/N 68043742AA; Daimler/Mercedes MB 236.12, 236.14, 236.41; FIAT 9.55550-AV1; Fiat Chrysler 8&9 Speed ATF, AW-1, Dex-VI, P/N 05127382, P/N 68157995AA/AB, SP-4, P/N 68171866AA, SP-IV, P/N 68171866AA, SP-IV, P/N 68171869AA; FORD/Lincoln/Mercury P/N XT-10-QLV [LV], P/N XT-6-QSP or -DSP, Spec WSS-M2C922-A1; GM Dex HP; GM/GMC/Opel/Saturn AW1, P/N 88863400; Honda/Acura DW-1, ATF Type 3.0; Honda 082000-9017 (ATF Type 3.1); Hyundai/Kia NWS-9638 T-5, WS, spec NWS-9638; P/N 040000C90SG, SP4-M1 / SP-IV / SP-IV-RR, SPH-VI; Isuzu SCS; Jaguar 02JDE 26444 / Fluid 8432; JASO M315, Class 1A-LV; Jeep ATF LGF8; Land Rover P/N TYK500050, LR0022460-AW-1, P/N LR0022460: LV, LR023288/023289 Maserati P/N 231603; Mazda FW 6A EL, FW 6AX EL, FZ; Mercon LV; Mitsubishi ATF-J3, SP-IV, Dia Queen ATF-MA1, Dia Queen ATF-PA; Nissan/Infinity Matic-S / Matic-W; Porsche P/N 000 043 304 00; Saab P/N 93 165 147 - AW-1; Shell 3353/134/1375.4; Subaru WS Suzuki Matic S; Toyota/Lexus/Scion WS; Volvo P/N 31 256 774, 31 256 775; VW/Audi G 052 533, G 055 005 (-A, A2),

G 055 540 (A2), G 055 162 A2 or A6,

G 060 162 A2 ZF Lifequard 6/8/9

Art.-N° **G063 GERMAN ADLER ATF 9-8**

Contents

- 1 l bottle
- 4 | canister
- 5 I canister
- 20 I pail
- 60 I drum
- 200 I drum

Description

- synthetic automatic transmission fluid especially developed for modern ZF 6-, 8- and 9- speed
- highest quality features
- high load capacity and extremely wear reducing
- excellent low- temperature switching behavior
- minimal evaporation losses
- adapted friction characteristics for sport gear changes
- no effect on sealing materials
- good ageing, oxidation and thermal stability
- excellent protection against foaming

Specification / Recommendation

BMW L12108 (83 22 2 152 426) BMW 83 22 2 305 397 BMW 83 22 2 289 720 (ATF3+) Chrysler 68157995AA FIAT 9.55550-AV5 Honda Type 3.1 Jaguar 02JDE 26444 Jeep ATF LGF8 Land Rover LR 023288/232289 MB 236.82 Mopar 68157995AA VW/Audi G 060 162 A1/A2/A6, G 055 162 (A2, A6) VW G 055 540 (A2) ZF Lifeguardfluid 8 (S671 090 312) ZF Lifeguardfluid 9 (AA01.500.001)

Art.-N° **G017 GERMAN ADLER ATF 9-9 F**

Contents

- 1 l bottle
- 4 I canister 5 | canister
- 20 I pail
- 60 I drum
- 200 I drum

Description

- synthetic automatic transmission fluid especially developed for Mercedes-Benz-9-automatic transmission (9G-Tronic)
- extremely shear stable with modern anti-wear additives
- high load capacity and extremely wear reducing
- excellent low-temperature switching behavior
- minimal evaporation losses
- no effect on sealing materials
- good ageing, oxidation and thermal stability
- excellent protection against foaming

Specification / Recommendation

ZF Lifeguard 6 (S671 090 255)

MB 236.16/236.17 MB 236.41 Aisin AW F8FXX DSIH 6p805 (Geely, Ssangyong, Mahindra 6sp) Hyundai NWS-9638 Hyundai/Kia SP-IV, SPH-IV, SP-IV RR JASO 1-A-LV Mitsubishi ATF-J3, ATF-PA Mopar 68218925AA Nissan Matic S, Matic W Saab 93 165 147 Volvo 6 speed MY 2011-2013 (P/N 31256774 or 31256675) VW G 052 540, G 055 005, G 055 162 ZF TE-ML 13 ZF 6 Speed (S671 090 255)



Art.-N° G100 GERMAN ADLER ATF 10 F

Contents

- 1 l bottle
- 4 I canister
- 5 I canister
- 20 I pail
- 60 I drum
- 200 l drum

Description

- synthetic automatic transmission fluid especially developed for 6, 8- and 10-automatic transmission (6-8-10G-Tronic)
- ultra low viscosity for high fuel economy
- extremely shear stable with modern anti-wear additives
- high load capacity and extremely wear reducing
- excellent low- temperature switching behavior
- minimal evaporation losses
- no effect on sealing materials
- good ageing, oxidation and thermal stability
- excellent protection against foaming

Specification / Recommendation

ATF 10 F

Aisin Warner AW-2 BMW 83 22 2 413 477 (ATF 7) Ford WSS-M2C949-A Ford Mercon ULV Ford P/N XT-12-ULV [ULV] Ford Motorcraft XT-12-QULV GM Dexron ULV GM 19352619 Mazda ATF A7

Nissan Matic P, P/N 999MP-MTP10P PSA 16 350 560 80 Volvo P/N 31 492 172 Volvo P/N 31 492 173 VW G 053 001 A2 VW G 060 540 A2

Art.-N° **G055** GERMAN ADLER ATF CVT

Contents

- 1 l bottle
- 4 | canister
- 5 I canister
- 20 I pail
- 60 I drum
- 200 I drum

Description

- synthetic automatic transmission fluid
- especially designed for the use in modern
- (CVT = Continuous Variable Transmission) transmissions
- fulfills the unique requirements of belt and chain CVT's
- excellent metal/metal friction behaviour
- optimal low-temperature properties
- most stable friction behaviour during whole operation life
- reliable power transmission/low friction losses are always granted
- outstanding wear protection under high loads
- good ageing and oxidation stability
- excellent protection against foaming

Specification / Recommendation

O MANUAL

ATF CVT

BMW 8322 0 429 154 BMW 8322 0 429 159 Chrysler/Dodge/Jeep

NS-2 Chrysler/Dodge/

Jeep/Mopar CVT+4 Daihatsu Ammix CVT

DC/DFC/DFE Daihatsu TC

ELFMATIC CVT Ford CVT 23, 30

Ford WSS-M2C928-A

Ford WSS-M2C933-A GM/Saturn DEX-CVT

Honda ATF-Z1*, HCF2

Honda HMMF*

Hyundai/Kia SP-III (CVT model)

Hyundai/Kia CVT-J1 Hyundai CVTF JASO M358

Mazda JWS 3320

MB 236.20

MB A 001 989 46 03

Mini Cooper EZL799/EZL799A/ZF CVT V1

Mercon C

Mitsubishi CVTF-J1 (MMC Diaqueen CVT

Fluid J1)

Mitsubishi (Diaqueen) SP-III (CVT

model only)

Mitsubishi CVTF-J4 & J4+ (MMC

Diagueen CVT Fluid J4 & J4+)

Nissan NS-1, NS-2, NS-3

Punch CVT

Subaru ECVT, iCVT, iCVT FG / NS-2

Subaru Lineartronic ECVT

Subara Lineartronic iCVT

Subaru Lineartronic High Torque (HT)

Subaru Lineartronic chain CVTF/CVTF II Suzuki CVTF TC, CVT Green 1/2/1V, NS-2, CVTF 3320

Toyota CVTF TC, CVTF FE

VW/Audi TL521 16 (G 052 516 A2)

VW/Audi TL521 80 (G 052 180 A1/A2/A6)

*use in Honda with starting clutch is

not recommended



Art.-N° **G035** GERMAN ADLER ATF DSG F

UPDATE

A MICHIE

ATF DSG P

Contents

- 1 l bottle
- 4 | canister
- 5 I canister
- 20 I pail 60 I drum
- 200 I drum

Description

- synthetic ATF for double clutch transmission (DCT)
- developed for the latest generation of DCT
- extremely high wear resistance
- high thermal stability
- excellent viscosity
- good temperature behaviour
- low pour point
- foamless even under difficult conditions
- high oxidation stability
- carrying capacity
- optimum friction characteristics
- neutral to metals and sealing materials

Specification / Recommendation

Audi/Volkswagen/ Seat/Skoda -G 052 182 A2/A6 (TL 52 182), G 052 529 A2/A6 (TL 52 529), Ġ 055 529 (TL 52 529-C) BMW - DCTF-1 (83 220 440 214), DCTF-1+, DCTF-2,



83 22 2 148 579 and 83 22 2 446 673 Borg Warner

BYD DCTs, Q/Byd-A1909.0058-2013

Bugatti Veyron

Citroen/Peugeot- 6DCT451 (PSA 9734.S2)

Changan DCTF

Chrysler Powershift 6-Speed (Getrag),

68044345 EA & GA

Eaton PS-278

Ferrari 7-Speed (Getrag),- TF DCT-F3

Fiat 9.55550-MZ6

Ford WSS-M2C200-D2/XT-11-QDC

Ford/Nissan Powershift 6-Speed (GFT),

Ford - WSS-M2C-936-A, part #

1490763/1490761

Ford WSS-M2C218-1A, -F-DC, part #

KU7J M2C218AA

Geely 7 Speed Mercedes Benz - MB 236.25, MB

236.21, MB236.22, MB 236.24 and MB 239.21

Mitsubishi - TC-SST 6-Speed (GFT),

MZ320065 DiaQueen SSTF-1

DCT Transmissionoil for ZF

Peugot/Citroen DCS 6-Speed, 9734.S2

Porsche - 043 207 29, 043 207 30, 000 043 20, 000 043 305 13,

999 917 080 01

Porsche - 000 043 210 44,

971 094 307 02A

Renault 77 11 785 243 (DW5)

Renault EDC 6-Speed (Getrag), EDC 7

Renault - BOT 450

Volvo Powershift 6-Speed (GFT)/1161838/1161839

VW G 052 536, 055 536 VW Audi G 052 512

VW (Audi, Seat, Skoda) 6-Speed VW/Audi TL 52529/G 052 529 A2 or

A6 (fluid)/DSG 7= S-tronic 7/7-Speed

VW (Audi, Seat, Skoda)

VW/Audi G 055 529 A1/A3/A3

VW/Audi TL 521 82/G 052 182 A2 or

A6 (fluid) ZF TE-ML 11 (ZF004743)

ZF Lifequard Fluid 8.2

Art.-N° G009 GERMAN ADLER GEAR OIL SAE 75W SYNT

Contents

- 1 l bottle
- 4 I canister
- 5 I canister
- 20 I pail
- 60 l drum
- 200 l drum

Description

- high performance low friction gear oil
- for lubrication of synchronized and nonsynchronized standard transmissions
- excellent high pressure- and wear protection properties
- very good properties in corrosion- and rust protection
- low foaming tendency and excellent aging stability
- high viscosity index and low pour point care for easy gear changing even at lot temperatures
- reduced oil consumption and extended oil drain intervals
- specially recommended for commercial vehicles with BMW, VW and Mercedes Benz manual transmissions

Specification / Recommendation

API GL-4 BMW MTF LT-2/-3/-4 FORD WSS-M2C200-D2 Fiat MZ 7 GM 1940764/ W16612 MB 235.10 PSA B71 2316 (HBVFE), PSA 9730 A8 Renault DC4 DW5 (C6DCT 250 dry DCT9) Special Gear Oil, MTF 94 Special Honda MTF/MTF-II Tranself TRT Volvo 97308/97309 VW G 052 527 A2, G 070 726 A2, G 052 178 VW G 052 512, G 052 726, VW G 060 726 VW G 055 512 A2

Art.-N° **G066**

GERMAN ADLER GEAR OIL SAE 75W-80 SYNT

Contents

1 l bottle

- 4 | canister
- 5 I canister
- 20 I pail
- 60 I drum
- 200 l drum

Description

- high performance low friction gear oil for lubrication of synchronized and nonsynchronized standard transmissions
- excellent high pressure- and wear protection properties
- very good properties in corrosion- and rust protection
- low foaming tendency and excellent aging stability
- high viscosity index and low pour point care for easy gear changing even at lot temperatures
- reduced oil consumption and extended oil drain intervals
- specially recommended for commercial vehicles with BMW, VW and Mercedes Benz manual transmissions

Specification / Recommendation

API GL-4 BMW MTF LT-1/-2/ -3/-4Fiat 9.55550-MZ6 FORD WSS-M2C200-C/ D2/+112C186-A GM 1940182/1940764/ 1940768 MB 235.10 NISSAN MT-XZ/ MT-XZ TL (JR Type) PSA B 71 2330 (EZL 848) + B71 2315 Special Gear Oil, MTF 94 Special Honda MTF/MTF-II/MTF-III Tranself NFJ, NFP, TRJ, TRT, TRZ, TRP, Volvo 97308/97309

VW G 009 317, VW G 052 171, G 052 178 VW G 052 512, G 052 726, VW G 060 726 VW G 50, G 052 527 A2, G 070 726 A2 VW G052 549

Art.-N° **G007** GERMAN ADLER GEAR OIL SAE 75W-90 SYNT TS-4

Contents

Description

- 1 l bottle
- 4 | canister
- 5 I canister
- 20 I pail
- 60 I drum
- 200 I drum
- high scuffing load carrying capacity and good wear protection
- excellent cold flow properties
- steady multigrade properties by high shear stability
- fuel efficient low friction properties
- excellent corrosion and oxidation protection, low foaming tendency
- for lubrication of heavily loaded axle drives, steering transmissions and transfer boxes of motor vehicles and contruction machines
- for synchronized and non-synchronized manual gears

Specification / Recommendation

API GL-4 MAN 341 E-1, Z-2 MB 235.1 ZF TE-ML 02B, 16A, 17A, 19C



GERMAN ADLER GEAR OIL SAE 75W-90 SYNT TS Art.-N° **G008**

Contents

1 l bottle

- 4 | canister
- 5 I canister
- 20 I pail
- 60 I drum
- 200 I drum

Description

- reducing the frictional resistance in gearing
- effective protection against early wear
- smooth running gear shifting at low temperatures
- lasting protection against corrosion and deposits
- total operational reliability at long using periods
- for highly loaded hypoid gears with great offset and for all-wheel drives
- manual gears, power dividers and intermediate gear boxes

Specification / Recommendation

API GL-5 MAN 342 Typ M-1 MB 235.0 MIL-L-2105 D Volvo 97310 ZF TE-ML 05A, 07A, 16B/C/D, 17B, 19B



GERMAN ADLER GEAR OIL SAE 75W-90 SYNT LS-5 Art.-N° **G004**

UPDATE

Contents

Description

- 1 | bottle
- 4 | canister
- 5 I canister
- 20 I pail
- 60 I drum 200 I drum

- outstanding oxidation stability
- extreme load-carrying capacity
- excellent anti-stick-slip characteristics
- endurable protection against corrosion and deposits
- special addidivation for noise reduction
- for axle gears with self locking differentials in motor vehicles and commercial cars
- LS-gear oil recommanded for agriculture, forestry and construction industry
- suitable in hypoid gears without locking differential

Specification / Recommendation

API GL-5 Arvin Meritor Axles Liebherr MAN 342 M1 MB 235.0 Volvo 97310 ZF TE-ML 05C, 12C, 16E, 21C



GERMAN ADLER GEAR OIL SAE 75W-90 SYNT Art.-N° **G002**

Contents

- 1 | bottle
- 4 | canister
- 5 I canister
- 20 l pail 60 l drum
- 200 I drum

Description

- fully synthetic high performance low friction gear oil
- covers the extreme high requirements of transaxle drives
- good gear operation at low temperatures
- excellent cold flow properties
- good synchronizing characteristics
- high ageing stability

Specification / Recommendation

API GL-4/GL-5/MT-1 MAN 3343 MAN M 342 M1/M2 MB 235.6 MIL-PRF-2105 D/E **SAE J2360** Scania STO 1:0 Volvo STD 1273.21, 1273.10 ZF TE-ML 02B, 05A, 07A, 08, 12E, 16B, 17A/B, 19B, 21A



Art.-N° **G001 GERMAN ADLER GEAR OIL SAE 80W-90**

Contents

1 l bottle

4 | canister 5 I canister

20 I pail 60 I drum

200 I drum

Description

- multi grade EP gear oil
- excellent wear and corrosion protection/shear stability
- good cold flow properties
- high ageing stability
- low foaming tendency
- assured corrosion protection
- elastomer compatibility

Specification / Recommendation

API GL-4 MAN 341 E-1 MB 235.1 ZF TE-ML 06L, 08, 16A, 17A, 19A, 19C, 24A



Art.-N° **G003 GERMAN ADLER GEAR OIL SAE 80W-90 GL-5**

Contents

- 1 l bottle
- 4 | canister
- 5 I canister
- 20 I pail
- 60 I drum
- 200 I drum

Description

- specially designed gear oil for high-loaded hypoid gears with wide offset
- for power take-off gears, intermediate gears and secondary gears in motor vehicles and construction machines
- specially applies to rear axles with hypoid gearing
- good cold flow properties and high aging stability
- high shear stability and low foaming tendency
- assured corrosion protection and elastomer compatibility

Specification / Recommendation

API GL-5 MAN 342 M-2 (160.000 km oil change) MB 235.0 MB 235.6 MIL-L-2105 D ZF TE-ML 05A, 07A 08, 12E, 16B-D, 17B, 19B, 21A



GERMAN ADLER GEAR OIL SAE 80W-90 LS-5 Art.-N° **G006**

Contents

- 1 l bottle
- 4 | canister
- 5 I canister
- 20 I pail
- 60 I drum
- 200 I drum

Description

- special gear oil for axle transmissions with Limited-Slip-Differentials
- assures optimal operation reliability and long lifetime of the aggregates to be lubricated
- outstanding oxidation stability
- extreme load-carrying capacity
- excellent anti-stick-slip characteristics
- endurable protection against corrosion and deposits
- special addidivation for noise reduction

Specification / Recommendation

API GL-5 MAN 342 M1 MB 235.0 Volvo 97310 ZF TE-ML 05C. 12C, 16E, 21C



Art.-N° **G000** GERMAN ADLER GEAR OIL SAE 80W-90 SYNT

Contents

1 l bottle

- 4 l canister 5 I canister
- 20 I pail
- 60 I drum
- 200 I drum

Description

- high performance multi grade gear oil
- for synchronized and non-synchronized manual gears
- also for steering gears, transfer gears, normal/hypoid teethed axle drives, including rear axles with outer planetary gears
- high wear protection within whole operation temperature range
- good shifting characteristics
- assured corrosion protection
- excellent wear and corrosion protection

Specification / Recommendation

API GL-4/GL-5 Ford WSP-M2C197-A MAN 3343 Typ M MAN M342 M1/M2 MB 235.0 MB 235.6 MIL-L-2105D/E **SAE J2360** Scania STO 1:0 Volvo 1273.10, 1273.21 ZF TE-ML 01, 05A,

07A, 08, 12A, 12E, 16B/C, 17B, 19B, 21A



Art.-N° **G005 GERMAN ADLER** GEAR OIL SAE **85W-90** EP

Contents

Description

- 1 l bottle
- 4 | canister
- 5 I canister
- 20 I pail
- 60 I drum
- 200 I drum
- high performance multi grade gear oil
- for passenger cars, trucks, busses, off-road and farm equipment
- provides maximum wear protection
- especially designed for high-loaded hypoid/power take-off gears
- excellent wear and corrosion protection
- good gear noise absorption
- low foam tendency even at high speed
- high shear stability

Specification / Recommendation

API GL-5 MAN 342 M-2 (160.000 km oil change) MB 235.0 MB 235.6 MIL-L-2105 D ZF TE-ML 05A, 07A 08, 12E, 16B-D, 17B, 19B, 21A



Art.-N° **G012** GERMAN ADLER GEAR OIL SAE 75W-140 SYNT

UPDATE

Contents

- 1 l bottle
- 5 I canister
- 20 I pail 60 I drum
- 200 I drum
- 4 | canister

Description

- fully synthetic special gear oil for axle transmissions with Limited-Slip-Differentials
- outstanding oxidation stability
- extreme load-carrying capacity
- excellent anti-stick-slip characteristics
- endurable protection against corrosion and deposits
- special addidivation for noise reduction

Specification / Recommendation

API GL-5 BMW LS Rear Axles Ford WSL-M2C192-A MB 235.61 Nissan GTR limited slip axles ZF TE-ML 05C, 12D, 16G, 21D



Art.-N° **G016 GERMAN ADLER GEAR OIL SAE 85W-140**

Contents

- 1 l bottle
- 4 | canister
- 5 I canister
- 20 I pail
- 60 I drum
- 200 I drum

Description

- high performance multi grade gear oil
- for passenger cars, trucks, busses, off-road and farm machinery
- provides maximum wear protection
- especially designed for high-loaded hypoid/power take-off gears
- excellent corrosion protection
- good gear noise absorption
- low foam tendency even at high speed
- high shear stability
- low foaming tendency

Specification / Recommendation

API GL-5 MAN 342 M-2 (160.000 km oil change) MB 235.0 MB 235.6 MIL-L-2105 D ZF TE-ML 05A, 07A, 08, 12E, 16B-D, 17B, 19B, 21A



HYDRAULIC- AND STEERING FLUIDS

Art.-N° **S501 GERMAN ADLER LH-M PLUS**

Contents

1 l bottle

- 4 I canister 5 I canister
- 20 I pail 60 I drum
- 200 I drum

Description

- high performance special hydraulic fluid
- especially designed for central hydraulics, power-steerings, convertible top actuation, hydro pneumatic chassis and shock absorbers
- excellent viscosity and temperature behaviour
- high shear stability
- outstanding ageing and oxidation stability
- excellent anti-wear and anti-corrosion properties
- good sealing compatibility

Specification / Recommendation

DIN 51524 part 3 ISO 7308 FIAT 9.55597 IVECO 18-1823 NH 610 A PSA B71 2710 SDFG OF1611S



Art.-N° **S502 GERMAN ADLER ZH-M PLUS**

Contents

- 1 l bottle
- 4 | canister
- 5 I canister
- 20 I pail
- 60 I drum

200 I drum

Description

- high performance special hydraulic fluid
- especially designed for central hydraulics, power-steerings, convertible top actuation, hydro pneumatic chassis and shock absorbers
- excellent viscosity and temperature behaviour
- high shear stability
- outstanding ageing and oxidation stability
- excellent anti-wear and anti-corrosion properties
- good sealing compatibility

Specification / Recommendation

Chrysler MS-1872 Chrysler MS-5931, P/N 04883077 Chrysler MS-9602, ATF+4 **DEXRON III DEXRON IID** Ford M2C195-A GM P/N 89021184 GM 9985010, P/N 1052884 Hyundai/Kia PSF-3 MB 236.3, P/N 000 989 88 03 Mitsubishi PS Fluid

Mitsubishi Diamond SPIII Nissan PSF-II Saab P/N (45) 30 09 800 Subaru P/N K0209A0080

Toyota PSF Type EH, P/N 008886-01

Art.-N° S509 GERMAN ADLER ZH-M PLUS F SYNT

Contents

- 1 l bottle
- 4 I canister
- 5 I canister
- 20 I pail
- 60 I drum
- 200 l drum

Description

- synthetic high performance special hydraulic
- especially designed for central hydraulics, power-steerings, convertible top actuation, hydro pneumatic chassis and shock absorbers
- excellent viscosity and temperature behaviour
- high shear stability
- outstanding ageing and oxidation stability
- excellent anti-wear and anti-corrosion properties
- good sealing compatibility

Specification / Recommendation

Audi P/N G002000, G002012 Chrysler MS-1872, MS-5931, P/N 04883077 Chrysler MS-9602, ATF+4 Chrysler MS-10838, P/N 05142893AA Ford M2C195-A, M2C204-A (end. temp. range) GM 9985010, P/N 10 GM 9985835, P/N 12





Art.-N° **B119 GERMAN ADLER BRAKE FLUID DOT 4**

Contents

0.25 I bottle

- 0.5 l bottle
 - 1 l bottle
 - 5 I canister
- 25 I pail
- 60 I drum 200 I drum

Description

- high performance brake fluid
- fully synthetic glycol base
- for use in hydraulic brake and clutch system
- high oxidation and corrosion inhibitors

Specification / Recommendation

FMVSS 116 SAE J 1704 ISO 4925 Class 3 & 4



Art.-N° **B114 GERMAN ADLER BRAKE FLUID DOT 5.1**

Contents

- 0.25 I bottle 0.5 I bottle
- 1 | bottle
- 5 I canister
- 25 I pail
- 200 I drum
- 60 I drum

Description

- high performance brake fluid
- fully synthetic glycol base
- for use in hydraulic brake and clutch system
- high oxidation and corrosion inhibitors

Specification / Recommendation

FMVSS 116 **SAE J 1703 SAE J 1704** ISO 4925 Class 3, 4 & 5.1





INDUSTRIAL OILS/HYDRAULIC FLUIDS

Art.-N° **H004 GERMAN ADLER HLP 22**

Contents

Description

20 I pail 60 I drum 200 I drum

- multi-purpose lube for hydraulic systems, gearboxes and bearings
- improves corrosion protection, ageing properties and wear protection
- good air release and minimal foaming tendency
- good compatibility with material coatings and elastomers
- excellent high pressure and shear stability
- very high viscosity index
- good filterability

Specification / Recommendation

DIN 51 524-2 (HM) AIST 126 ASTM D 6158 (HM) Bosch Rexroth RDE 90235 Eaton E-FDGN-TBoo2-E Fives P68, P69, P70 (HM)



GB 111158.1-2011 (L-HL, L.HM) GM LS-2 ISO 11158 (HM) JCMAS P041 HK Hydraulic specification Parker (Denison) HF-0, HF-1, HF-2 (HM)

SAE MS 1004 (HM) SEB 181222

Art.-N° **H005 GERMAN ADLER HLP 32**

Contents

Description

20 I pail 60 I drum 200 I drum

- multi-purpose lube for hydraulic systems, gearboxes and bearings
- improves corrosion protection, ageing properties and wear protection
- good air release and minimal foaming tendency
- good compatibility with material coatings and elastomers
- excellent high pressure and shear stability
- very high viscosity index
- good filterability

Specification / Recommendation

DIN 51 524-2 (HM) **AIST 126** ASTM D 6158 (HM) Bosch Rexroth RDE 90235 Eaton E-FDGN-TBoo2-E Fives P68, P69, P70 (HM)



Hydraulic specification Parker (Denison) HF-0, HF-1, HF-2 (HM) SAE MS 1004 (HM)

SEB 181222

JCMAS PO41 HK

INDUSTRIAL OILS/HYDRAULIC FLUIDS

Art.-N° **H006 GERMAN ADLER HLP 46**

Contents

20 I pail 60 I drum 200 I drum

Description

- multi-purpose lube for hydraulic systems, gearboxes and bearings
- improves corrosion protection, ageing properties and wear protection
- good air release and minimal foaming tendency
- good compatibility with material coatings and elastomers
- excellent high pressure and shear stability
- very high viscosity index
- good filterability

Specification / Recommendation

DIN 51 524-2 (HM) **AIST 126** ASTM D 6158 (HM) Bosch Rexroth RDE 90235 Eaton E-FDGN-TBoo2-E Fives P68, P69, P70 (HM)

SEB 181222



GM LS-2 ISO 11158 (HM) JCMAS P041 HK

Hydraulic specification Parker (Denison) HF-0, HF-1, HF-2 (HM) SAE MS 1004 (HM)

Art.-N° **H007 GERMAN ADLER HLP 68**

Contents

20 I pail

60 I drum 200 I drum

Description

- multi-purpose lube for hydraulic systems, gearboxes and bearings
- improves corrosion protection, ageing properties and wear protection
- good air release and minimal foaming tendency
- good compatibility with material coatings and elastomers
- excellent high pressure and shear stability
- very high viscosity index
- good filterability

Specification / Recommendation

DIN 51 524-2 (HM) **AIST 126** ASTM D 6158 (HM) Bosch Rexroth RDE 90235 Eaton E-FDGN-TBoo2-E Fives P68, P69, P70 (HM) GB 111158.1-2011 (L-HL, L.HM) GM LS-2 ISO 11158 (HM) JCMAS PO41 HK Hydraulic specification Parker (Denison) HF-0, HF-1, HF-2 **SAE MS 1004 (HM)** SEB 181222

GERMAN ADLER HLP 100 Art.-N° **H008**

Contents

20 I pail 60 I drum 200 l drum

Description

- multi-purpose lube for hydraulic systems, gearboxes and bearings
- improves corrosion protection, ageing properties and wear protection
- good air release and minimal foaming tendency
- good compatibility with material coatings and elastomers
- excellent high pressure and shear stability
- very high viscosity index
- good filterability

Specification / Recommendation

DIN 51 524-2 (HM) AIST 126 ASTM D 6158 (HM) Bosch Rexroth RDE 90235 Eaton E-FDGN-TBoo2-E Fives P68, P69, P70 (HM) GB 111158.1-2011 (L-HL, L.HM) GM LS-2 ISO 11158 (HM) JCMAS P041 HK Hydraulic specification Parker (Denison) HF-0, HF-1, HF-2 (HM) SAE MS 1004 (HM) SEB 181222







RADIATOR ANTIFREEZE/COOLANT

Art.-N° **W017 GERMAN ADLER** ANTIFREEZE

UPDATE

Contents

Description

1.5 l bottle 5 I canister

- high-quality radiator antifreeze, anti-corrosion and coolant
- all year use/concentrated
- especially designed to fulfill the requirements of cast iron and aluminium
- free from nitrite, amine and phosphate
- prevents from deposits, corrosion and foaming
- prevents from cavitation
- minimized foaming tendencies
- compatible with sealing materials
- colour: blue

Specification / Recommendation

ASTM D 3306 SAE J 1034 AS 2108-2004 **AFNOR NF R15-601** BS 6580:2010



Art.-N° **W018** GERMAN ADLER ANTIFREEZE G

UPDATE

Contents

1.5 | bottle 5 | canister

Description

- high-quality radiator antifreeze, anti-corrosion and coolant
- all year use/concentrated
- especially designed to fulfill the requirements cast iron and aluminium
- free from nitrite, amine and phosphate
- prevents from deposits, corrosion and foaming
- prevents from cavitation
- minimized foaming tendencies
- compatible with sealing materials
- colour: green

Specification / Recommendation

ASTM D 3306 SAE J 1034 AS 2108-2004 **AFNOR NF R15-601** BS 6580:2010



GERMAN ADLER ANTIFREEZE READY MIX -5 °C Art.-N° **W175**

Contents 1.5 | bottle

5 I canister

Description

- high-quality radiator antifreeze, anti-corrosion and coolant ASTM D3306
- all year use/ready to use for radiator
- especially designed to fulfill the requirements of cast iron and aluminium
- free from nitrite, amine and phosphate
- prevents from deposits, corrosion and foaming
- prevents from cavitation
- minimized foaming tendencies
- compatible with sealing materials
- colour: blue

Specification / Recommendation

ASTM D4985

SAE J 1034

BS 6580

AFNOR NF R 15-601

TYPE 1

AS 2108

CUNA NC 956-16

JIS K 2234

ÖNORM V 5123

UNE 26361



GERMAN ADLER ANTIFREEZE READY MIX -5°C G Art.-N° **W185**

Contents

5 I canister

Description

1.5 | bottle

- high-quality radiator antifreeze, anti-corrosion and coolant ASTM D3306
- all year use/ready to use for radiator
- especially designed to fulfill the requirements of cast iron and aluminium
- free from nitrite, amine and phosphate
- prevents from deposits, corrosion and foaming
- prevents from cavitation
- minimized foaming tendencies
- compatible with sealing materials
- colour: green

Specification / Recommendation



ASTM D4985 SAE J 1034

BS 6580 **AFNOR NF R 15-601**

TYPE 1

AS 2108 CUNA NC 956-16

JIS K 2234

ÖNORM V 5123

UNE 26361





Art.-N° W041 GERMAN ADLER ANTIFREEZE READY MIX -25 °C

UPDATE

Contents

Description

1.5 | bottle 5 | canister

- high-quality radiator antifreeze, anti-corrosion and coolant
- all year use/ready to use for radiator
- especially designed to fulfill the requirements of cast iron and aluminium
- free from nitrite, amine and phosphate
- prevents from deposits, corrosion and foaming
- prevents from cavitation
- minimized foaming tendencies
- compatible with sealing materials
- colour: blue

Specification / Recommendation

ASTM D 3306 SAE J 1034 AS 2108-2004 AFNOR NF R15-601 BS 6580:2010



Art.-N° W042 GERMAN ADLER ANTIFREEZE READY MIX -25 °C G

UPDATE

Contents

Description

1.5 | bottle 5 | canister

- high-quality radiator antifreeze, anti-corrosion and coolant
- all year use/ready to use for radiator
- especially designed to fulfill the requirements of cast iron and aluminium
- free from nitrite, amine and phosphate
- prevents from deposits, corrosion and foaming
- prevents from cavitation
- minimized foaming tendencies
- compatible with sealing materials
- colour: green

Specification / Recommendation

ASTM D 3306 SAE J 1034 AS 2108-2004 AFNOR NF R15-601 BS 6580:2010



Art.-N° W051 GERMAN ADLER ANTIFREEZE READY MIX -38 °C

UPDATE

Contents

Description

- 1.5 | bottle 5 | canister
- high-quality radiator antifreeze, anti-corrosion and coolant
- all year use/ready to use for radiator
- especially designed to fulfill the requirements of cast iron and aluminium
- free from nitrite, amine and phosphate
- prevents from deposits, corrosion and foaming
- prevents from cavitation
- minimized foaming tendencies
- compatible with sealing materials
- colour: blue

Description

Specification / Recommendation

ASTM D 3306 SAE J 1034 AS 2108-2004 AFNOR NF R15-601 BS 6580:2010



Art.-N° W052 GERMAN ADLER ANTIFREEZE READY MIX -38°C G

UPDATE

Contents

1.5 | bottle 5 | canister

- high-quality radiator antifreeze, anti-corrosion and coolant
- all year use/ready to use for radiator
- especially designed to fulfill the requirements of cast iron and aluminium
- free from nitrite, amine and phosphate
- prevents from deposits, corrosion and foaming
- prevents from cavitation
- minimized foaming tendencies
- compatible with sealing materials
- colour: green

Specification / Recommendation

ASTM D 3306 SAE J 1034 AS 2108-2004 AFNOR NF R15-601 BS 6580:2010



Art.-N° W014 GERMAN ADLER ANTIFREEZE 12 PLUS

UPDATE

Contents

Description

1.5 | bottle 5 | canister

- long life radiator antifreeze, anti-corrosion and coolant
- all year use/concentrated
- free from nitrites, amines, phosphonates and silicates
- provides reliable protection for aluminium and cast iron engines
- fulfills the VW-specification VW TL 774-F (G12+)
- backward compatible to G12 and G11 (TL`774 C/D)
- silicate free additive technology
- prevents reliably from deposits
- very good and long lasting anti-corrosion properties
- prevents from cavitation
- minimized foaming tendencies
- colour: pink

Specification / Recommendation

VW TL 774 D, VW TL 774 F MAN 324 SNF MB 325.3 Ford WSS-M97B44-D GM 6277M AS 2108-2004 ASTM D 3306, ASTM D 4985 AFNOR NF R15-601 BS 6580:2010 SAE J 1034



for more specification see product information

Art.-N° W145 GERMAN ADLER ANTIFREEZE READY MIX 12 PLUS -5°C

Contents

Description

1.5 | bottle 5 | canister

- long life radiator antifreeze, anti-corrosion and coolant
- all year use/concentrated
- free from nitrites, amines, phosphonates and silicates
- provides reliable protection for aluminium and cast iron engines
- fulfills the VW-specification VW TL 774-F (G12+)
- backward compatible to G12 and G11 (TL 774 C/D)
- silicate free additive technology
- prevents reliably from deposits
- very good and long lasting anti-corrosion properties
- prevents from cavitation
- minimized foaming tendencies
- colour: pink

Specification / Recommendation

ASTM D3306 ASTM D4985 SAE J 1034 MB 325.3 Opel GM QL 130100 JIS K 2234, JASO M325 AUDI, SEAT, SKODA VW TL 774 F (G12+) VW TL 774 D (G12) ISUZU RENAULT 41-01-001/ -S Type D GM 1899 M MAZDA

Volvo



for more specification see product information

Art.-N° W048 GERMAN ADLER ANTIFREEZE READY MIX 12 PLUS -25°C

UPDATE

Contents

Description

1.5 | bottle 5 | canister

- long life radiator antifreeze, anti-corrosion and coolant
- all year use/ready to use for radiator
- free from nitrites, amines, phosphonates and silicates
- provides reliable protection for aluminium and cast iron engines
- fulfills the VW-specification VW TL 774-F (G12+)
- backward compatible to G12 and G11 (TL 774 C/D)
- silicate free additive technology
- prevents reliably from deposits
- very good and long lasting anti-corrosion properties
- prevents from cavitation
- minimized foaming tendencies
- colour: pink

Specification / Recommendation

VW TL 774 D, VW TL 774 F MAN 324 SNF MB 325.3 Ford WSS-M97B44-D GM 6277M AS 2108-2004 ASTM D 3306, ASTM D 4985 AFNOR NF R15-601 BS 6580:2010 SAE J 1034



for more specification see product information

Art.-N° **W049** GERMAN ADLER ANTIFREEZE READY MIX 12 PLUS -37 °C

UPDATE

Contents

Description

1.5 l bottle 5 I canister

- long life radiator antifreeze, anti-corrosion and coolant
- all year use/ready to use for radiator
- free from nitrites, amines, phosphonates and silicates
- provides reliable protection for aluminium and cast iron
- fulfills the VW-specification VW TL 774-F (G12+)
- backward compatible to G12 and G11 (TL 774 C/D)
- silicate free additive technology
- prevents reliably from deposits
- very good and long lasting anti-corrosion properties
- prevents from cavitation
- minimized foaming tendencies
- colour: pink

Specification / Recommendation

VW TL 774 D, VW TL 774 F MAN 324 SNF MB 325.3 Ford WSS-M97B44-D GM 6277M AS 2108-2004 ASTM D 3306, ASTM D 4985 **AFNOR NF R15-601** BS 6580:2010

SAE J 1034

for more specification see product information



GERMAN ADLER ANTIFREEZE GA13 Art.-N° **W013**

UPDATE

Contents

Description

1.5 l bottle

5 | canister

- long life radiator antifreeze, anti-corrosion and coolant
- all year use/concentrated
- fulfills the VW-specification VW TL 774-F (G13)
- free from nitrites, amines and phosphonates
- provides reliable protection for aluminium and cast iron engines
- backward compatible to G12++ and G12+ (TL 774 G/F)
- prevents reliably from deposits
- very good and long lasting anti-corrosion properties
- prevents from cavitation
- minimized foaming tendencies
- colour: pink

Specification / Recommendation

VW TL 774 J Audi Bentley Lamborghini Seat/Skoda



GERMAN ADLER ANTIFREEZE GA13 READY MIX -5 °C Art.-N° **W135**

Contents

Description

1.5 | bottle 5 I canister

- long life radiator antifreeze, anti-corrosion and coolant
- all year use/concentrated
- fulfills the VW-specification VW TL 774-F (G13)
- free from nitrites, amines and phosphonates
- provides reliable protection for aluminium and cast iron engines
- backward compatible to G12++ and G12+ (TL 774 G/F) prevents reliably from deposits
- very good and long lasting anti-corrosion properties
- prevents from cavitation
- minimized foaming tendencies
- colour: pink

Specification / Recommendation

ASTM D 3306 AUDI, (BENTLEY, BUGATTI, LAMBORGHINI) SEAT, SKODA G 13 VW TL 774 J



Art.-N° W061 GERMAN ADLER ANTIFREEZE GA13 READY MIX -35°C

UPDATE

Contents

Description

1.5 | bottle 5 | canister

- long life radiator antifreeze, anti-corrosion and coolant
- ready to use for -35°C/all year use
- fulfills the VW-specification VW TL 774-F (G13)
- free from nitrites, amines and phosphonates
- provides reliable protection for aluminium and cast iron engines
- backward compatible to G12++ and G12+ (TL 774 G/F)
- prevents reliably from deposits
- very good and long lasting anti-corrosion properties
- prevents from cavitation
- minimized foaming tendencies
- colour: pink

Specification / Recommendation

VW TL 774 J Audi Bentley Lamborghini Seat/Skoda









Art.-N° **D110 GERMAN ADLER OCTANE BOOSTER**

Contents Description

300 ml metal can - high quality additive for gasoline engines

- improves octane number up to 7 points
- maximum engine performance
- excellent acceleration of engine
- for 70L gasoline
- lowers fuel consumption



Art.-N° **D120** GERMAN ADLER CETANE BOOSTER

Contents Description

300 ml metal can

- high quality additive for diesel engines
- improves cetan number and ignition quality
- maximum engine performance
- plus special purification addive
 lowers fuel consumption



Art.-N° **D130 GERMAN ADLER INJECTION CLEANER**

Contents Description

- 300 ml metal can high quality additive for injection system
 - made for gasoline engines
 - top cleanliness properties against deposit
 - excellent protection against corrosion
 - for 60L gasoline
 - very good anti-sludge properties



GERMAN ADLER ENGINE FLUSH Art.-N° **D140**

Description **Contents**

- 300 ml metal can high quality additive to clean engine
 - 300ml made for 6L oil in gasoline or diesel engines
 - highly effective detergent and dispersant
 - dissolve sludge and dirt
 - optimal engine cleanliness



Art.-N° **D150** GERMAN ADLER RADIATOR LEAK STOP

Contents Description

- 300 ml metal can high quality additive for radiators
 - suitable for all types of radiators
 - stops leakages very fast
 - long time sealing behaviour
 - excellent anticorrosion agent
 - compatible to all types of coolants



GERMAN ADLER ANTI SMOKE Art.-N° **D160**

Contents Description

- 300 ml metal can high quality additive for diesel engines
 - maximum engine performance
 - increases engine power and engine life
 - provide the self-cleaning of the DPF
 - for 80 L diesel
 - lowers fuel consumption





Art.-N° D170 GERMAN ADLER DPF CLEANER

Contents Description

300 ml metal can - high-quality additive for diesel engines to reduce sludge formation

- created especially for cleanliness of the DPF
 optimizes engine power and life time of the DPF
- regular application is recommended.



Art.-N° D180 GERMAN ADLER RADIATOR CLEANER

Contents Description

300 ml metal can - high-quality additive for clean out the entire cooling system

- removes corrosion and sludge deposits



Art.-N° D190 GERMAN ADLER DIESEL SYSTEM CLEANER

Contents Description

300 ml metal can - high-quality additive for cleaning of nozzles and valves of diesel engines

- optimizes the engine power and extends the life time of the engine-



Art.-N° **D200** GERMAN ADLER OIL TREATMENT

Description **Contents**

- 300 ml metal can high-quality additive to improve the viscosity of motor oils
 - improves sealing and reduces oil consumption and engine wear
 - suitable for gasoline and diesel engines with catalyst,
 - diesel particulate filter and turbocharger



Art.-N° **D215** GERMAN ADLER CATALYST CLEANER

Contents Description

- 300 ml metal can high-quality additive to protects the catalyst against sludge deposits
 - inlet valves and combustion chamber will be cleaned
 - fuel system will be protected against corrosion
 - reduces the CO₂ emissions and protects the environment





GERMAN ADLER HEAD OFFICE FRANKFURT

GERMAN ADLER GmbH

Kennedyallee 93 60596 Frankfurt am Main Germany

Phone: +49 69 697 692 10 Fax: +49 69 697 692 15 export@German-Adler.com info@German-Adler.com www.German-Adler.com



TRANSPORT

PACKAGING FOR CONTAINERS

0.3 bottle 0.4 bottle 0.5 bottle 1 bottle 1 bottle 1 canister 5 canister 10 canister 20 pail 25 pail 60 drum 200 drum 1000 IBC	2184/2688 2160 1920 1176 672 336 270 60 90 75 9x2 4x2 2	piece/pallete = piece/pallete piece/pallete piece/pallete piece/pallete piece/pallete piece/pallete piece/pallete piece/pallete	91/112 cartons 180 cartons 160 cartons 98 cartons 56 cartons 84 cartons 90 cartons
Brake fluid 0.25 bottle 0.5 bottle 1 bottle	2340	piece/pallete =	195 cartons
	1680	piece/pallete =	100 cartons
	1020	piece/pallete =	136 cartons

Container loading

20' container 10 pallets/container 40' container 20 pallets/container

PACKAGING FOR TRUCK

0.3 bottle 0.4 bottle 0.5 bottle 1.5 bottle 4 canister 5 canister 20 pail 25 pail	1680/2016 2160 1920 672 200 150 30	piece/pallete = piece/pallete = piece/pallete = piece/pallete = piece/pallete = piece/pallete = piece/pallete piece/pallete	70/84 cartons 180 cartons 160 cartons 56 cartons 50 cartons 50 cartons
60 l drum	6x2	piece/pallete	
200 l drum	4x2	piece/pallete	
1000 IBC	1	piece/pallete	
Brake fluid			
0.25 bottle	2340	piece/pallete =	135 cartons
0.5 l bottle	1680	piece/pallete =	70 cartons
1 l bottle	1020	piece/pallete =	102 cartons

Truck loading

max. loading 22,500 Kg

Pallets only stackable for container loading. Not available for truck shipment.



PRODUCT CATALOG



Made in Germany www.German-Adler.com, Frankfurt am Main/GERMANY

